

QuickShip

 *Shipping in 48 hours*



May 2024

Why Choose Williams

Founded in 1921, H.E. Williams, Inc. is a third-generation, family-owned and -operated lighting manufacturer. With over a century in business, we produce and ship products from our factory in Carthage, Missouri. Exceptional quality and customer service makes us the most trusted brand in lighting. Working with Williams is simply easier and friendlier.

Benefits

- Competitively-priced LED products
- Easy to install and service
- Ideal for design-build projects
- On-hand inventory to support immediate job requirements
- Williams quality you know and trust

Program Guidelines

- Submit order for QuickShip (QS) items only
- Reference QuickShip in the subject line of all requests
- Consult factory for individual product quantities over 100 pieces



Recessed

BP Backlit Flat Panel



FieldSELECT™ LUMENS + CCT ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ *Fixture Standards: 80 CRI, Selectable CCT 3,500K/4,000K/5,000K, 0-10V dimming, universal voltage, ships in 4-pack cartons*

BP-14-LS/8CS-QS-DIM-UNV	1' x 4'	Selectable lumens 3,100/3,600/4,700
BP-14-LS/8CS-EM/8W-QS-DIM-UNV	1' x 4'	Selectable lumens 3,100/3,600/4,700 ■ 8-watt EM battery
BP-22-LS/8CS-QS-DIM-UNV	2' x 2'	Selectable lumens 3,100/3,500/4,200
BP-22-LS/8CS-EM/8W-QS-DIM-UNV	2' x 2'	Selectable lumens 3,100/3,500/4,200 ■ 8-watt EM battery
BP-24-LS/8CS-QS-DIM-UNV	2' x 4'	Selectable lumens 3,500/4,700/5,700
BP-24-LS/8CS-EM/8W-QS-DIM-UNV	2' x 4'	Selectable lumens 3,500/4,700/5,700 ■ 8-watt EM battery Extended lead times apply.

FT FieldSELECT Troffer



FieldSELECT™ LUMENS + CCT ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ *Fixture Standards: 80 CRI, Selectable CCT 3,500K/4,000K/5,000K, frosted acrylic lens, 0-10V dimming, universal voltage*

FT-22-LS/8CS-AF-QS-DIM-UNV	2' x 2'	Selectable lumens 2,500/3,400/4,400
FT-24-LS/8CS-AF-QS-DIM-UNV	2' x 4'	Selectable lumens 4,100/5,800/6,800
FT EM/10W KIT-QS		10-watt EM battery kit

LT Troffer



Fixture Standards: 80 CRI, frosted acrylic lens, 0-10V dimming, universal voltage

LT-14-L47/835-AF-QS-DIM-UNV	1' x 4'	4,700 lumens ■ 3500K CCT
LT-14-L47/840-AF-QS-DIM-UNV	1' x 4'	4,700 lumens ■ 4000K CCT
LT-22-L39/835-AF-QS-DIM-UNV	2' x 2'	3,900 lumens ■ 3500K CCT
LT-22-L39/840-AF-QS-DIM-UNV	2' x 2'	3,900 lumens ■ 4000K CCT
LT-24-L40/835-AF-QS-DIM-UNV	2' x 4'	4,000 lumens ■ 3500K CCT
LT-24-L40/840-AF-QS-DIM-UNV	2' x 4'	4,000 lumens ■ 4000K CCT
LT-24-L64/835-AF-QS-DIM-UNV	2' x 4'	6,400 lumens ■ 3500K CCT
LT-24-L64/840-AF-QS-DIM-UNV	2' x 4'	6,400 lumens ■ 4000K CCT

PT Shallow Plenum Troffer



Fixture Standards: Diffuse ribbed acrylic round lens, 0-10V dimming, universal voltage

PT-22-L43/835-RA-QS-DIM-UNV	2' x 2'	4,300 lumens ■ 3500K CCT
PT-22-L43/840-RA-QS-DIM-UNV	2' x 2'	4,300 lumens ■ 4000K CCT
PT-24-L49/835-RA-QS-DIM-UNV	2' x 4'	4,900 lumens ■ 3500K CCT
PT-24-L49/840-RA-QS-DIM-UNV	2' x 4'	4,900 lumens ■ 4000K CCT

Downlights



4RCD | 6RCD Round Commercial Downlight



FieldSELECT™ LUMENS + CCT ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ *Fixture Standards: 90 CRI, Selectable CCT 2,700K/3,000K/3,500K/4,000K/5,000K, 0-10V dimming, universal voltage*

4RCD-LS/9CS-WH-QS-DIM-UNV	Selectable lumens 500/800/1,000 ■ White trim
4RCD-LS/9CS-SS-QS-DIM-UNV	Selectable lumens 500/800/1,000 ■ Semi-specular trim
4RCD-N-F1-QS	New construction pan with hardware
6RCD-LS/9CS-WH-QS-DIM-UNV	Selectable lumens 1,200/1,700/2,200 ■ White trim
6RCD-LS/9CS-SS-QS-DIM-UNV	Selectable lumens 1,200/1,700/2,200 ■ Semi-specular trim
6RCD-N-F1-QS	New construction pan with hardware

4FDR | 6FDR FieldSELECT Round Downlight



FieldSELECT™ LUMENS + CCT ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ *Fixture Standards: 80 CRI, Selectable CCT 3,000K/3,500K/4,000K, 0-10V dimming, universal voltage*

4FDR-LS/8CS-CS-QS-DIM-UNV	Selectable lumens 1,000/1,500/2,000 ■ CS Reflector finish
4FDR-N-F1-QS	New construction pan with hardware
6FDR-LS/8CS-CS-QS-DIM-UNV	Selectable lumens 1,000/1,600/2,000 ■ CS Reflector finish
6FDR-N-F1-QS	New construction pan with hardware
4FDR/6FDR EM/10W KIT-QS	10-watt EM battery kit

4DR | 6DR Round Pro Downlight



Fixture Standards: 80 CRI, 3500K CCT, 1% dimming, open reflector, wide distribution, 1/2" standard flange, new construction pan with hardware

4DR-TL-L10/835-QS-DIM1-UNV-OW-OF-__-N-F1	1,000 lumens ■ Specify reflector color: WH, BL, or CS
4DR-TL-L20/835-QS-DIM1-UNV-OW-OF-__-N-F1	2,000 lumens ■ Specify reflector color: WH, BL, or CS
6DR-TL-L10/835-QS-DIM1-UNV-OW-OF-CS-N-F1	1,000 lumens ■ Clear semi-specular reflector
6DR-TL-L20/835-QS-DIM1-UNV-OW-OF-CS-N-F1	2,000 lumens ■ Clear semi-specular reflector



H.E. WILLIAMS, INC.

831 West Fairview Ave | Carthage, MO 64836

417-358-4065

hew.com

REV.05/15/24.JL