



LED Downlight Collection Product Guide

2 INCH

4 INCH

6 INCH

8 INCH



Series	2DR	2DS	2AR	2AS	4DR	4DS	4AR	4PR	4PS	M4PR	M4PS	V4DR	6DR	6DS	6AR	6PR	6PS	M6PR	M6PS	V6DR	8DR
Round	✓		✓		✓		✓	✓		✓		✓	✓		✓	✓		✓		✓	✓
Square		✓		✓		✓			✓		✓			✓			✓		✓		
Adjustable			✓	✓			✓								✓						
Shallow Plenum								✓	✓	✓	✓					✓	✓	✓	✓		
MRI										✓	✓							✓	✓		
New Construction	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Remodel	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓	✓	✓	✓	✓				✓
IC-Rated	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
1/2" Standard Flange	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
1/4" Mud-In Flange					✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓		
Zero-Flange Mud-In	✓	✓	✓	✓																	
Max Delivered Lumens	2500	2500	1500	1500	6000	4000	4000	3000	4000	4000	4000	4000	6000	5000	4000	5000	5000	5000	5000	6100	10,000
Beam Angles	8, 15, 40, 70	14, 20, 30, 50	15, 20, 35	15, 20, 35	10, 45, 65	25, 35, 60	20, 30, 45	25, 35, 65	30, 35, 75	25, 35, 65	30, 35, 75	25, 35, 50	10, 40, 65	25, 35, 65	25, 35, 55	25, 35, 85	30, 35, 85	25, 35, 85	30, 35, 85	25, 35, 55	35, 50, 65
IP65-Rated					✓	✓		✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Chicago Plenum (CCEA)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Energy Star	✓	✓			✓								✓								
Title 24 JAB Compliant	✓	✓			✓	✓							✓	✓							
WET/CC	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓
Sloped Ceiling Adapter					✓								✓								✓
Tunable White	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Tunable Color					✓	✓							✓	✓							
Dim to Warm	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
PoE	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓			✓	
	TRIMS																				
Open Anodized Reflector	✓	✓	✓		✓	✓	✓						✓	✓	✓						✓
Flush Lens	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Regressed Lens	✓	✓	✓	✓	✓	✓						✓	✓	✓							✓
Angled Lens	✓	✓	✓		✓	✓	✓	✓				✓	✓	✓	✓	✓					✓
Wall Wash (Kicker)	✓	✓			✓	✓						✓	✓	✓							✓
Dead-Front Shower Trim					✓			✓					✓			✓					
Tamper-Resistant												✓									✓