



DOWNLIGHT COLLECTION PRODUCT GUIDE

| | QUICKSHIP | | LITE | SPEC GRADE | | | | | | | | | | |
|--------------------------|-------------|-------------|-----------|------------|------------|-------|-------------|---------|------------|-------------|-------------|---------|-------------|---------|
| | | | | | | | | | | | | | | |
| | 4RCDD/6RCDD | 4FDDR/6FDDR | 4LDR/6LDR | 2D | 2A | V2D | 4D/6D | 4A/6A | 4P/6P | HM4/HM6 | HS4/HS6 | M4P/M6P | V4D/V6D | 8D |
| ROUND | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| SQUARE | | | | ✓ | ✓ | | ✓ | | ✓ | | | ✓ | | |
| ADJUSTABLE | | | | | ✓ | | | ✓ | | | | | | |
| SHALLOW PLENUM | | | | | | | | | ✓ | | | ✓ | | |
| MRI | | | | | | | | | | | | ✓ | | |
| MAX DELIVERED LUMENS | 1,000/2,200 | 2,000 | 3,000 | 2,500 | 1,500 | 1,800 | 8,000 | 4,000 | 7,000 | 4,000/6,000 | 4,000/6,000 | 5,000 | 3,700/5,600 | 8,000 |
| BEAM ANGLES | W | W | W | W, M, N, S | W, M, N | W | W, M, N, WW | W, M, N | W, M, N | W, M, N | W, M, N | W, M, N | W, M, N | W, M, N |
| OVERLAPPING FLANGE | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| SLIM FLANGE MUD-IN | | | | | | | ✓ | ✓ | ✓ | | | | | |
| ZERO FLANGE MUD-IN | | | | ✓ | ✓ | | | | | | | | | |
| MOUNTING | | | | | | | | | | | | | | |
| NEW CONSTRUCTION | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| REMODEL | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | | | | | ✓ |
| IC-RATED | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ |
| LISTINGS | | | | | | | | | | | | | | |
| IP65-RATED | | | | | | | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | |
| NSF | | | | | | | | | | ✓ | ✓ | | | |
| ISO 5 | | | | | | | | | | ✓ | ✓ | | ✓ | |
| MIL STD 461G | | | | | | | | | | | ✓ | | | |
| CHICAGO PLENUM (CCEA) | | | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ |
| TITLE 24 JA8 COMPLIANT | | | | ✓ | | | ✓ | | | | | | | |
| WET/CC | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| BAA COMPLIANT | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| BABA COMPLIANT | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| OPTIONS | | | | | | | | | | | | | | |
| SLOPED CEILING ADAPTER | | | | | | | Round only | | | | | | | ✓ |
| AIRTIGHT CONSTRUCTION | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| TUNABLE WHITE | | | | ✓ | ✓ | | ✓ | ✓ | ✓ | | | ✓ | ✓ | ✓ |
| TUNABLE RGBW | | | | | | | ✓ | | | | | | | |
| DIM TO WARM | | | | ✓ | ✓ | | ✓ | ✓ | ✓ | | | ✓ | ✓ | ✓ |
| FIELDSELECT | ✓ | ✓ | | | | | | | | | | | | |
| ANTI-MICROBIAL | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| EMERGENCY | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| IN-FIXTURE CONTROLS | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| TRIM | | | | | | | | | | | | | | |
| OPEN REFLECTOR | | | | Round only | Round only | | Round only | ✓ | | | | | | ✓ |
| OPEN + TOP DIFFUSER | ✓ | ✓ | ✓ | ✓ | | | ✓ | | | | | | | |
| FLUSH LENS | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | |
| REGRESSED LENS | | | | ✓ | ✓ | ✓ | ✓ | | | ✓ | ✓ | | ✓ | |
| ANGLED LENS | | | | ✓ | Round only | | ✓ | ✓ | Round only | | | | | |
| DEAD-FRONT SHOWER | | | | | | | Round only | | Round only | | | | | |
| TAMPER-RESISTANT | | | | | | ✓ | | | | | | | ✓ | |