



HIGH BAY PRODUCT GUIDE



GNR
NSF-Rated Round



GS
Slim



GA
Narrow Aisle



GH
Compact



GL
Low-Profile



GP
Performance

Click for
more info →

LUMEN OUTPUT	15,500 to 37,600	12,000 to 48,000	3,500 to 18,000	8,000 to 72,000	15,000 to 80,000	9,300 to 74,000
MAX EFFICACY	148 lm/W	155 lm/W	186 lm/W	187 lm/W	188 lm/W	140 lm/W
LENGTH	17" Round	2' 4'	4' 8'	2' 4'	4'	2'
AMBIENT TEMP	-40°C to 55°C	55°C Max	40°C Max	55°C Max	60°C Max	-35°C to 65°C
DISTRIBUTION	W	N M	N	N M	N M	N M W
ALUMINUM HOUSING	✓	✓			✓	✓
STEEL HOUSING			✓	✓		✓
LOW-PROFILE		✓	✓	✓	✓	
LISTINGS						
NSF CERTIFIED	✓					
IP66 RATED	✓					
UL 924			✓			
QUICKSHIP		✓				
BAA COMPLIANT	✓	✓	✓	✓	✓	✓
BABA COMPLIANT		✓	✓	✓	✓	✓
DLC QUALIFIED		✓		✓		
SHIELDING						
OPEN (NO LENS)		✓	✓	✓	✓	✓
ACRYLIC	✓	✓		✓	✓	
POLYCARBONATE	✓			✓		✓
MOUNTING						
CONTINUOUS ROW			✓			
SUSPENDED	✓	✓	✓	✓	✓	✓
SURFACE		✓	✓	✓		✓
OPTIONS						
UPLIGHT				✓	✓	✓
EMERGENCY	✓	✓	✓	✓	✓	✓
OCCUPANCY SENSOR		✓	✓	✓	✓	✓
WIREGUARD		✓		✓	✓	✓
IN-FIXTURE CONTROLS		✓	✓	✓	✓	✓