



STRIPS PRODUCT GUIDE

									
Click for more info →	FS FieldSELECT™	75 Narrow	75R Narrow – Round Lens	75S Narrow – Square Lens	75W Narrow – Wide Lens	75L Narrow – Flat Lens	76 Standard	76R Standard – Round Lens	GA Aisle Lighter
LUMEN OUTPUT	3,400 to 12,200	1,500 to 24,000	1,500 to 20,000	1,500 to 20,000	1,500 to 20,000	1,000 to 16,000	3,200 to 23,000	3,000 to 18,800	3,500 to 18,000
MAX EFFICACY	152 lm/W	192 lm/W	182 lm/W	182 lm/W	182 lm/W	154 lm/W	200 lm/W	154 lm/W	186 lm/W
LENGTH	4' 8'	2' 3' 4' 8'	2' 3' 4' 8'	2' 3' 4' 8'	2' 3' 4' 8'	2' 4' 8'	4' 8'	4' 8'	4' 8'
MAX AMBIENT TEMP	35°C	50°C	50°C	50°C	50°C	25°C	50°C	50°C	40°C
LISTINGS									
BAA	✓	✓	✓	✓	✓	✓	✓	✓	✓
BABA	✓	✓	✓	✓	✓	✓	✓	✓	✓
QUICKSHIP	✓		✓	✓					
UL 924		✓	✓	✓	✓	✓	✓	✓	✓
DLC QUALIFIED	✓				✓			✓	
MOUNTING									
CONTINUOUS ROWS		✓	✓	✓	✓	✓	✓	✓	✓
AIRCRAFT CABLES		✓	✓	✓	✓	✓	✓	✓	✓
Y-HANGERS	✓	✓	✓	✓	✓	✓	✓	✓	✓
T-BAR CLIP							✓	✓	✓
STEM & CANOPY							✓	✓	✓
SURFACE MOUNT	✓	✓	✓	✓	✓	✓	✓	✓	✓
45° BRACKET		✓	✓	✓	✓	✓			
OPTIONS									
TUNABLE WHITE		✓	✓	✓	✓	✓			
FIELDSELECT	✓								
EMERGENCY	✓	✓	✓	✓	✓	✓	✓	✓	✓
OCCUPANCY SENSOR		✓	✓	✓	✓	✓	✓	✓	✓
IN-FIXTURE CONTROLS		✓	✓	✓	✓	✓	✓	✓	✓
10KV PROTECTION		✓	✓	✓	✓	✓			✓
WIREGUARD		✓	✓	✓	✓	✓	✓	✓	