



High Bay Product Guide



GS
Slim



GA
Narrow Aisle



GH
Compact



GL
Low-Profile



GP
Performance

Click for more info →

Lumen Output	12,000 to 48,000	3,500 to 11,000	8,000 to 72,000	15,000 to 40,000	9,300 to 74,000
Max Efficacy	155 lm/W	151 lm/W	154 lm/W	162 lm/W	140 lm/W
Length	2' 4'	4' 8'	2' 4'	4'	2'
Ambient Temp	55°C Max	40°C Max	55°C Max	-40°C to 60°C	-35°C to 65°C
Distribution	N M	N	N M	N M	N M W
Lens	Open Acrylic	Open	Open Acrylic PC	Open Acrylic	Open PC
Housing	Aluminum	CRS	Steel	Aluminum	Aluminum Steel
Low-Profile	✓	✓	✓	✓	
Continuous Row		✓			
QuickShip					
BAA Compliant	✓	✓	✓	✓	✓
DLC Qualified			✓		
	Options				
Uplight			✓	✓	✓
Emergency	✓	✓	✓	✓	✓
Surface Mount	✓	✓	✓		✓
Occupancy	✓	✓	✓	✓	✓
Wireguard	✓		✓	✓	✓
In-Fixture Controls	✓	✓	✓	✓	✓