

Wraps Product Guide

Click for	NW Narrow	AW Angled Narrow	17 Low-Profile	18 Wide Low-Profile	39 Linear	39W Wide Linear	AVX Vandal-Resistant
Lumen Output	3,400 to 9,300	3,400 to 9,300	2,700 to 11,000	9,000	3,000 to 16,800	3,000 to 16,800	2,500 to 20,000
Length	4′	4'	2' 4' 8'	4'	4' 8'	4' 8'	2' 4' 8'
Width	4-3/8″	5-13/16″	10-3/4″	16-3/4″	10-3/16″	12-1/16″	11″
Shielding	Ribbed Diffuse Acrylic	Ribbed Diffuse Acrylic	Frosted Prismatic Acrylic	Frosted Prismatic Acrylic	Frosted Ribbed Acrylic	Frosted Ribbed Acrylic	Polycarbonate
Low-Profile			\checkmark	\checkmark			\checkmark
Vandal-Resistant							\checkmark
IK10 Rated							\checkmark
ADA Compliant					\checkmark	\checkmark	\checkmark
QuickShip	\checkmark		\checkmark				
BAA Compliant	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
				Mounting			
Surface	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Suspended	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Aircraft Cable		\checkmark			\checkmark	\checkmark	\checkmark
Wall					\checkmark	\checkmark	\checkmark
Row			\checkmark	✓	\checkmark	\checkmark	\checkmark
Corner							\checkmark
				Options			
Tunable White							\checkmark
PoE							\checkmark
WET/CC							\checkmark
Emergency	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Occupancy		√	\checkmark	\checkmark	\checkmark	√	\checkmark
In-Fixture Controls		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark