



IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6CR-TL-L30-835-XXX-DIM-UNV-OW-BL-XX_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] GEN FROM BALLABS TEST NO. 20685.0

[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC

[ISSUEDATE] 26-JAN-2021

[MANUFAC] WILLIAMS INDOOR

[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO

[LUMINAIRE] 1 BRIDGELUX V13 LED 6" ROUND SURFACE CYLINDER

[MORE] OPEN SEMI-SPEC SPUN ALUMINUM REFLECTOR (WIDE)

[LUMCAT] 6CR-TL-L30-835-xxx-DIM-UNV-OW-BL-xx

[_SEARCH_SOURCETYPE] LED

[_SEARCH_APPLICATION] Indoor, Classroom, Commercial, Corridor, Hotel, Industrial, Office, Downlight

[_SEARCH_MOUNTING] Surface

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1403
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	50
Total Luminaire Watts	27.8
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.22
Spacing Criterion (90-270)	1.22
Spacing Criterion (Diagonal)	0.94
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.37 ft (Diameter)
Luminous Width (90-270)	0.37 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4254	4254	4254
55	1311	1311	1311
65	162	162	162
75	0	0	0
85	0	0	0

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6CR-TL-L30-835-XXX-DIM-UNV-OW-BL-XX_.IES

CANDELA TABULATION

	<u>0</u>
0	1204.049
5	1239.971
10	1277.223
15	1303.832
20	1361.706
25	1484.107
30	1162.805
35	204.223
40	53.218
45	29.270
50	15.300
55	7.317
60	3.326
65	0.665
70	0.665
75	0.000
80	0.000
85	0.000
90	0.000

IES INDOOR REPORT**PHOTOMETRIC FILENAME : 6CR-TL-L30-835-XXX-DIM-UNV-OW-BL-XX_.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	492.05	N.A.	35.10
0-30	1125.49	N.A.	80.20
0-40	1369.75	N.A.	97.60
0-60	1401.41	N.A.	99.90
0-80	1402.89	N.A.	100.00
0-90	1402.89	N.A.	100.00
10-90	1283.62	N.A.	91.50
20-40	877.70	N.A.	62.60
20-50	901.98	N.A.	64.30
40-70	32.96	N.A.	2.30
60-80	1.48	N.A.	0.10
70-80	0.17	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1402.89	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	119.27
10-20	372.78
20-30	633.44
30-40	244.26
40-50	24.28
50-60	7.38
60-70	1.31
70-80	0.17
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT

PHOTOMETRIC FILENAME : 6CR-TL-L30-835-XXX-DIM-UNV-OW-BL-XX_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	102	101	100	98	98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	86	83	82
4	98	91	85	81	96	90	85	81	87	83	80	85	82	79	84	81	78	77
5	93	85	79	75	92	84	79	75	82	78	74	81	77	74	79	76	73	72
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	76	67	61	57	75	66	61	57	66	60	57	65	60	57	64	60	57	55
10	73	63	58	54	72	63	57	54	62	57	54	61	57	53	61	56	53	52


IES INDOOR REPORT
PHOTOMETRIC FILENAME : 6CR-TL-L30-835-XXX-DIM-UNV-OW-BL-XX_.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	3H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	4H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	6H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	8H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	12H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
4H	2H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	3H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	4H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	6H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	8H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	12H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
8H	4H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	6H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	8H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	12H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
12H	4H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	6H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	8H	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2

Maximum UGR = 1.2

POLAR GRAPH



Maximum Candela = 1484.107 Located At Horizontal Angle = 0, Vertical Angle = 25
1 - Vertical Plane Through Horizontal Angles (90 - 270)
2 - Horizontal Cone Through Vertical Angle (25) (Through Max. Cd.)