



UL Verification Services Inc.  
7036 Snowdrift Road  
Allentown, PA 18106  
610-774-1300



## Indoor Distribution Test Report

Relevant Standards  
IES LM-79-2008, ANSI C82.77-2002

**Prepared For**  
**H E Williams Inc**  
831 W Fairview Ave  
PO Box 837  
Carthage, MO 64836-0837  
United States

**Catalog Number**  
**6DR-L20/835-DIM-UNV-O-N-OF-CS**  
Order Number  
12326812  
Test Number  
12326812.05

Test Date

2018-06-06

Prepared By

Cordaryl Cousar, Technician

Approved By

Alexa Lambert, Project Handler

The results contained in this report pertain only to the tested sample.  
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.  
This report must not be used by the client to claim product certification, approval, or endorsement by  
NVLAP, NIST, or any agency of the Federal Government.



**Luminaire Description:** Black formed aluminum housing, specular reflector, no lens enclosure  
**Lamp:** One white LED  
**Mounting:** Recessed  
**Ballast/Driver:** Philips XI025C070V054DSM5

**Luminaire**



**Luminaire Characteristics**

Luminous Diameter: 6.00 in.

**Summary of Results**

|                         |               |
|-------------------------|---------------|
| Total Luminaire Output: | 2026 Lumens   |
| Luminaire Efficacy:     | 106.1 lm/w    |
| Maximum Candela:        | 22004 Candela |

**Test Conditions**

|                   |           |
|-------------------|-----------|
| Test Temperature: | 25.0 °C   |
| Voltage:          | 120.0 VAC |
| Current:          | 0.1601 A  |
| Power:            | 19.09 W   |
| Power Factor:     | 0.994     |
| Frequency:        | 60 Hz     |
| Current THD:      | 9.67 %    |

Laboratory results may not be representative of field performance  
Ballast factors have not been applied



## Distribution - Goniophotometer

### Distribution Test Conditions

| Temperature | Voltage   | Current  | Power   | Power Factor | Frequency | Current THD |
|-------------|-----------|----------|---------|--------------|-----------|-------------|
| 25.0 °C     | 120.0 VAC | 0.1601 A | 19.09 W | 0.994        | 60 Hz     | 9.67 %      |

### Summary of Results

#### Spacing Criteria

0-180: 0.16

90-270: 0.16

Total Lumen Output:

2026 Lumens


Luminaire Efficacy:

106.1 lm/w

Maximum Candela:

22004 Candela

### Polar Plot



### Zonal Lumen Summary

| Zone  | Lumens | % of Luminaire | Zone    | Lumens | % of Luminaire | Zone    | Lumens | % of Luminaire |
|-------|--------|----------------|---------|--------|----------------|---------|--------|----------------|
| 0-5   | 355.2  | 17.5%          | 60-65   | 0.8    | 0.0%           | 120-125 | 0      | 0.0%           |
| 5-10  | 397.3  | 19.6%          | 65-70   | 0.5    | 0.0%           | 125-130 | 0      | 0.0%           |
| 10-15 | 304.0  | 15.0%          | 70-75   | 0.3    | 0.0%           | 130-135 | 0      | 0.0%           |
| 15-20 | 289.6  | 14.3%          | 75-80   | 0.2    | 0.0%           | 135-140 | 0      | 0.0%           |
| 20-25 | 272.0  | 13.4%          | 80-85   | 0.1    | 0.0%           | 140-145 | 0      | 0.0%           |
| 25-30 | 213.5  | 10.5%          | 85-90   | 0.1    | 0.0%           | 145-150 | 0      | 0.0%           |
| 30-35 | 153.9  | 7.6%           | 90-95   | 0      | 0.0%           | 150-155 | 0      | 0.0%           |
| 35-40 | 24.4   | 1.2%           | 95-100  | 0      | 0.0%           | 155-160 | 0      | 0.0%           |
| 40-45 | 6.3    | 0.3%           | 100-105 | 0      | 0.0%           | 160-165 | 0      | 0.0%           |
| 45-50 | 4.2    | 0.2%           | 105-110 | 0      | 0.0%           | 165-170 | 0      | 0.0%           |
| 50-55 | 2.4    | 0.1%           | 110-115 | 0      | 0.0%           | 170-175 | 0      | 0.0%           |
| 55-60 | 1.4    | 0.1%           | 115-120 | 0      | 0.0%           | 175-180 | 0      | 0.0%           |

| Zone   | Lumens | % of Luminaire |
|--------|--------|----------------|
| 0-40   | 2010   | 99.2%          |
| 0-60   | 2024   | 99.9%          |
| 0-90   | 2026   | 100.0%         |
| 90-180 | 0      | 0.0%           |



### Candela Tabulation

Horizontal Angle (Degrees)

Vertical Angle (Degrees)

|     | 0     | 22.5  | 45    | 67.5  | 90    | 112.5 | 135   | 157.5 | 180   | 202.5 | 225   | 247.5 | 270   | 292.5 | 315   | 337.5 |
|-----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0   | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 | 22000 |
| 5   | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  | 9830  |
| 10  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  | 3526  |
| 15  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  | 2032  |
| 20  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  | 1558  |
| 25  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  | 1021  |
| 30  | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   | 755   |
| 35  | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   | 242   |
| 40  | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    | 21    |
| 45  | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    | 13    |
| 50  | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     | 8     |
| 55  | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     | 4     |
| 60  | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     | 2     |
| 65  | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     |
| 70  | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     | 1     |
| 75  | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 80  | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 85  | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 90  | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 95  | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 100 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 105 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 110 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 115 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 120 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 125 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 130 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 135 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 140 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 145 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 150 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 155 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 160 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 165 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 170 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 175 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |
| 180 | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     | 0     |

### Average Luminance (cd/m<sup>2</sup>)

Horizontal Angle (Degrees)

Vertical Angle (Degrees)


|    | 0       | 45      | 90      |
|----|---------|---------|---------|
| 0  | 1206000 | 1206000 | 1206000 |
| 45 | 1041    | 1041    | 1041    |
| 55 | 379     | 379     | 379     |
| 65 | 158     | 158     | 158     |
| 75 | 94      | 94      | 94      |
| 85 | 91      | 91      | 91      |



### Coefficients of Utilization - Zonal Cavity Method

| Effective Floor Cavity Reflectance 20% |   |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Ceiling Cavity Reflectance             | 80  |     |     |     | 70  |     |     |     | 50  |     |     | 30  |     |     | 10  |     |     | 0   |
| Wall Reflectance                       | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 0   |
| Room Cavity Ratio (RCR)                | ** Values are expressed as percent of total lumen output delivered to the task surface ** |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 0                                      | 119   | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1                                      | 115   | 113 | 111 | 109 | 112 | 111 | 109 | 107 | 107 | 105 | 104 | 103 | 102 | 101 | 99  | 99  | 98  | 96  |
| 2                                      | 111   | 107 | 104 | 101 | 109 | 105 | 103 | 100 | 102 | 100 | 98  | 99  | 98  | 96  | 97  | 95  | 94  | 93  |
| 3                                      | 107   | 102 | 98  | 95  | 105 | 101 | 97  | 95  | 98  | 95  | 93  | 96  | 94  | 92  | 94  | 92  | 90  | 89  |
| 4                                      | 103   | 98  | 94  | 90  | 102 | 97  | 93  | 90  | 95  | 91  | 89  | 93  | 90  | 88  | 91  | 89  | 87  | 86  |
| 5                                      | 100   | 94  | 89  | 86  | 99  | 93  | 89  | 86  | 91  | 88  | 85  | 90  | 87  | 84  | 88  | 86  | 84  | 83  |
| 6                                      | 97  | 90  | 86  | 83  | 96  | 90  | 85  | 82  | 88  | 85  | 82  | 87  | 84  | 81  | 86  | 83  | 81  | 80  |
| 7                                      | 94  | 87  | 83  | 80  | 93  | 86  | 82  | 79  | 85  | 82  | 79  | 84  | 81  | 79  | 83  | 80  | 78  | 77  |
| 8                                      | 91  | 84  | 80  | 77  | 90  | 84  | 79  | 77  | 83  | 79  | 76  | 82  | 78  | 76  | 81  | 78  | 76  | 75  |
| 9                                      | 88  | 81  | 77  | 74  | 88  | 81  | 77  | 74  | 80  | 76  | 74  | 79  | 76  | 74  | 79  | 76  | 73  | 72  |
| 10                                     | 86  | 79  | 75  | 72  | 85  | 79  | 74  | 72  | 78  | 74  | 72  | 77  | 74  | 71  | 77  | 73  | 71  | 70  |


| Beam and Field Information |               |
|----------------------------|---------------|
| CIE Type:                  | Direct        |
| Center Beam Intensity:     | 22000 Candela |
| Central Cone Intensity:    | 16824 Candela |
| Beam Flux:                 | 319.5 Lumens  |
| Beam Angle (0-180):        | 9.2 Degrees   |
| Beam Angle (90-270):       | 9.2 Degrees   |
| Field Angle (0-180):       | 27.9 Degrees  |
| Field Angle (90-270):      | 27.9 Degrees  |





## ISOFootcandle Plot

Mounting Height - 8 Feet



Grid Lines in Units of Mounting Height

5 fc    2 fc    1 fc    0.5 fc    0.2 fc    0.1 fc