



IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L4-835-0-D-DIM-UNV_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] GEN FROM BALLABS TEST NO. 19927.0
[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC
[ISSUEDATE] 2023-07-14
[MANUFAC] WILLIAMS INDOOR
[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO 64836
[LUMINAIRE] CONTINUOUS COVE LUMINAIRE @ 0 DEGREE
[MORE] WITH FROSTED ACRYLIC LENS
[LUMCAT] CX-3-08-L4-835-0-D-DIM-UNV
[LAMPCAT] 22 INCH LED ARRAYS
[_SEARCH_SOURCETYPE] LED
[_SEARCH_APPLICATION] INDOOR, CLASSROOM, EDUCATIONAL, ATRIUM
[_SEARCH_MOUNTING] COVE

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1515
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	123
Total Luminaire Watts	12.3
Ballast Factor	1.00
CIE Type	Indirect
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.22 ft
Luminous Width (90-270)	3.69 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	0	0	0
55	0	0	0
65	0	0	0
75	0	0	0
85	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L4-835-0-D-DIM-UNV_.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>
0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
15	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
30	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
35	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
40	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
45	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
50	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
55	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
60	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
65	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
70	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
75	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
80	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
85	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
90	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
95	0.782	1.173	4.299	25.014	29.313	30.095	27.359	27.359	28.140
100	19.933	29.704	42.211	63.707	72.696	67.615	62.925	63.707	66.052
105	80.122	90.284	92.629	105.526	113.734	114.907	107.871	106.699	107.871
110	135.230	134.449	137.966	147.737	149.691	163.371	155.554	151.645	148.128
115	170.797	175.096	180.567	184.085	187.993	207.926	196.592	193.465	191.511
120	211.444	215.352	222.387	225.905	230.986	248.964	239.193	238.412	232.940
125	251.700	257.563	261.080	269.288	275.150	283.749	282.576	281.013	273.587
130	291.175	303.291	302.118	311.108	315.798	324.005	324.396	323.614	313.453
135	326.350	342.375	338.857	350.191	356.054	365.434	360.744	364.653	353.709
140	361.917	375.987	376.769	384.976	391.620	403.346	398.265	396.310	391.620
145	393.965	404.518	409.208	415.462	423.278	435.394	430.704	424.451	426.405
150	423.278	436.958	439.303	444.774	453.373	469.788	461.971	452.200	459.626
155	455.327	467.443	468.616	471.351	481.904	497.147	489.330	478.387	485.031
160	480.341	493.238	490.893	492.457	503.791	516.689	510.435	497.929	502.228
165	497.538	514.344	512.390	510.435	520.597	531.150	524.896	512.390	514.735
170	508.872	524.506	524.506	523.333	532.713	540.921	534.667	518.643	520.597
175	510.435	529.586	532.322	531.541	540.921	547.565	540.139	519.425	520.206
180	530.759	530.759	530.759	530.759	530.759	530.759	530.759	530.759	530.759

IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L4-835-0-D-DIM-UNV_.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	0.00	N.A.	0.00
0-30	0.00	N.A.	0.00
0-40	0.00	N.A.	0.00
0-60	0.00	N.A.	0.00
0-80	0.00	N.A.	0.00
0-90	0.00	N.A.	0.00
10-90	0.00	N.A.	0.00
20-40	0.00	N.A.	0.00
20-50	0.00	N.A.	0.00
40-70	0.00	N.A.	0.00
60-80	0.00	N.A.	0.00
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	134.10	N.A.	8.90
90-120	321.01	N.A.	21.20
90-130	564.25	N.A.	37.30
90-150	1098.48	N.A.	72.50
90-180	1514.67	N.A.	100.00
110-180	1380.57	N.A.	91.10
0-180	1514.67	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	0.00
10-20	0.00
20-30	0.00
30-40	0.00
40-50	0.00
50-60	0.00
60-70	0.00
70-80	0.00
80-90	0.00
90-100	25.98
100-110	108.12
110-120	186.92
120-130	243.24
130-140	271.57
140-150	262.65
150-160	219.98
160-170	145.63
170-180	50.58


IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L4-835-0-D-DIM-UNV_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10	0
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8	0
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7	0
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6	0
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5	0
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4	0
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4	0
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3	0
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3	0
9	43	32	25	20	37	27	22	18	19	15	13	11	9	8	4	3	3	0
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2	0

POLAR GRAPH



Maximum Candela = 547.565 Located At Horizontal Angle = 112.5, Vertical Angle = 175
1 - Vertical Plane Through Horizontal Angles (112.5 - 292.5) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (175) (Through Max. Cd.)