



IES INDOOR REPORT

PHOTOMETRIC FILENAME : CX-3-08-L6-850-0-D-DIM-UNV_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] GEN FROM BALLABS TEST NO. 19927.0
 [TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC
 [ISSUEDATE] 2023-07-14
 [MANUFAC] WILLIAMS INDOOR
 [OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO 64836
 [LUMINAIRE] CONTINUOUS COVE LUMINAIRE @ 0 DEGREE
 [MORE] WITH FROSTED ACRYLIC LENS
 [LUMCAT] CX-3-08-L6-850-0-D-DIM-UNV
 [LAMPCAT] 22 INCH LED ARRAYS
 [_SEARCH_SOURCETYPE] LED
 [_SEARCH_APPLICATION] INDOOR, CLASSROOM, EDUCATIONAL, ATRIUM
 [_SEARCH_MOUNTING] COVE

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2388
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	132
Total Luminaire Watts	18.04
Ballast Factor	1.00
CIE Type	Indirect
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.22 ft
Luminous Width (90-270)	3.69 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	0	0	0
55	0	0	0
65	0	0	0
75	0	0	0
85	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L6-850-0-D-DIM-UNV_.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>
0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
15	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
30	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
35	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
40	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
45	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
50	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
55	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
60	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
65	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
70	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
75	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
80	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
85	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
90	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
95	1.232	1.849	6.779	39.440	46.219	47.451	43.137	43.137	44.370
100	31.429	46.835	66.555	100.449	114.622	106.611	99.216	100.449	104.146
105	126.331	142.354	146.051	166.387	179.329	181.177	170.085	168.236	170.085
110	213.222	211.990	217.536	232.942	236.024	257.592	245.267	239.105	233.559
115	269.301	276.080	284.707	290.254	296.416	327.845	309.974	305.044	301.962
120	333.391	339.554	350.646	356.192	364.204	392.551	377.145	375.912	367.285
125	396.865	406.109	411.655	424.596	433.840	447.397	445.549	443.084	431.375
130	459.106	478.210	476.361	490.535	497.930	510.871	511.487	510.255	494.232
135	514.569	539.835	534.289	552.160	561.404	576.194	568.799	574.961	557.706
140	570.647	592.832	594.065	607.006	617.482	635.970	627.959	624.877	617.482
145	621.180	637.819	645.214	655.074	667.399	686.502	679.107	669.247	672.329
150	667.399	688.967	692.665	701.292	714.850	740.732	728.407	713.001	724.710
155	717.931	737.035	738.884	743.197	759.836	783.870	771.545	754.290	764.766
160	757.371	777.707	774.010	776.475	794.346	814.682	804.822	785.102	791.881
165	784.486	810.985	807.903	804.822	820.845	837.483	827.623	807.903	811.601
170	802.357	827.007	827.007	825.158	839.948	852.890	843.030	817.763	820.845
175	804.822	835.018	839.332	838.100	852.890	863.366	851.657	818.996	820.228
180	836.867	836.867	836.867	836.867	836.867	836.867	836.867	836.867	836.867

IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L6-850-0-D-DIM-UNV_.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	0.00	N.A.	0.00
0-30	0.00	N.A.	0.00
0-40	0.00	N.A.	0.00
0-60	0.00	N.A.	0.00
0-80	0.00	N.A.	0.00
0-90	0.00	N.A.	0.00
10-90	0.00	N.A.	0.00
20-40	0.00	N.A.	0.00
20-50	0.00	N.A.	0.00
40-70	0.00	N.A.	0.00
60-80	0.00	N.A.	0.00
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	211.44	N.A.	8.90
90-120	506.15	N.A.	21.20
90-130	889.68	N.A.	37.30
90-150	1732.01	N.A.	72.50
90-180	2388.23	N.A.	100.00
110-180	2176.8	N.A.	91.10
0-180	2388.23	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	0.00
10-20	0.00
20-30	0.00
30-40	0.00
40-50	0.00
50-60	0.00
60-70	0.00
70-80	0.00
80-90	0.00
90-100	40.96
100-110	170.47
110-120	294.72
120-130	383.52
130-140	428.20
140-150	414.13
150-160	346.85
160-170	229.62
170-180	79.76


IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L6-850-0-D-DIM-UNV_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10	0
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8	0
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7	0
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6	0
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5	0
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4	0
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4	0
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3	0
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3	0
9	43	32	25	20	37	28	22	18	19	15	13	11	9	8	4	3	3	0
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2	0

POLAR GRAPH



Maximum Candela = 863.366 Located At Horizontal Angle = 112.5, Vertical Angle = 175
1 - Vertical Plane Through Horizontal Angles (112.5 - 292.5) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (175) (Through Max. Cd.)