



UL Solutions
7036 Snowdrift Road
Allentown, PA 18106
610-774-1300



Photometric Test Report

Relevant Standards

IES LM-79-2019, ANSI C82.77-10-2014, CIE 13.3-1995
CIE 15-2004, ANSI C78.377-2017, IES TM-30-2018

Prepared For

H E Williams Inc

Dean Vandergriff
831 W Fairview Ave
PO Box 837
Carthage
MO 64836-0837

Catalog Number

FT-14-2-8-3500K-AF-DIM-UNC (FT-14-LS-8CS-AF-DIM-UNV)

Order Number

15184934

Test Number

15184934.01

Test Date

2024-02-26

Prepared By

Dennis Kabana, Laboratory Technician

Approved By

Jesse Litchfield, Project Handler

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.

This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Table of Contents

Summary of Results	Page 3
Integrating Sphere Results	Page 4
Distribution Results	
Conditions / Summary of Results / Polar Plot / Zonal Lumens	Page 5
Candela Tabulation / Average Luminance	Page 6
Coefficients of Utilization / Cone of Light	Page 7
ISOFootcandle Plot	Page 8
Full TM-30 Report	Page 9

The device under test emits no detectable uplight, as defined by ANSI/IES LM-75-19.
For the purpose of this report, certain non-zero uplight readings have been assigned a zero value, in accordance with the requirements of ANSI/IES LM-75-19

Laboratory results may not be representative of field performance
Ballast factors have not been applied


Testing was performed in a 2-meter integrating sphere using the 4π geometry method.

Absorption correction was employed for Sphere measurement



Luminaire Description: Recessed 1 x 4 Lumen/Wattage selectable, CCT selectable, LED Troffer w/center frosted acrylic lens.
Lamp: 224 LEDs
Mounting: Recessed
Ballast/Driver: ISTAR ISC-030W-070DDSM-ADJ33

Luminaire



Luminaire Characteristics

Luminous Length: 47.00 in.
Luminous Width: 11.00 in.

Summary of Results

Integrating Sphere

Luminous Flux: 2685 Lumens
Efficacy: 157.41 lm/w
CCT: 3483 K
CRI (Ra): 81.4

Distribution

Total Luminaire Output: 2615 Lumens
Luminaire Efficacy: 153.4 lm/w
Maximum Candela: 921 Candela

Electrical Data at 120 VAC

Test Temperature: 24.5 °C
Voltage: 120.1 VAC
Current: 0.1437 A
Power: 17.06 W
Power Factor: 0.989
Frequency: 60 Hz
Current THD: 8.05 %



Color Quality - Integrating Sphere

Integrating Sphere Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
24.5 °C	120.1 VAC	0.1437 A	17.06 W	0.989	60 Hz	8.05 %


Summary of Results

Total Output:	2685 Lumens	Chromaticity (x):	0.4059
Efficacy:	157.4 lm/w	Chromaticity (y):	0.3905
CCT:	3483 K	Chromaticity (u'):	0.2362
CRI (Ra):	81.4	Chromaticity (v'):	0.5112
CRI (R9):	-0.9	TM-30 Rf:	83
Peak Wavelength:	598 nm	TM-30 Rg:	96
Dominant Wavelength:	555 nm	TM-30 Rcs,h1:	-13%
S/P Ratio:	1.5	Duv:	-0.0003
M/P Ratio:	0.58	WELL Building Standard v2	



Color Rendering Index Detail

Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.4	79.3	88.3	95.6	80.5	79.8	85.0	83.4	58.9	-0.9	73.6	80.2	65.8	81.3	97.9	71.6



Distribution - Goniophotometer


Distribution Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
25.2 °C	120.1 VAC	0.1436 A	17.05 W	0.989	60 Hz	8.05 %

Summary of Results

Spacing Criteria	Total Lumen Output:	2615 Lumens
0-180: 1.21	Luminaire Efficacy:	153.4 lm/w
90-270: 1.28	Maximum Candela:	921 Candela
Corrected UGR (Room Dimension: X=4H, Y=8H, Reflectances: 70/50/20%, S/H: 1)		
Crosswise: 19.2	Endwise: 20.1	

Polar Plot



Zonal Lumen Summary

Zone	Lumens	% of Luminaire	Zone	Lumens	% of Luminaire	Zone	Lumens	% of Luminaire
0-5	21.9	0.8%	60-65	179.2	6.9%	120-125	0	0.0%
5-10	65.0	2.5%	65-70	149.5	5.7%	125-130	0	0.0%
10-15	105.7	4.0%	70-75	114.7	4.4%	130-135	0	0.0%
15-20	142.5	5.4%	75-80	77.2	3.0%	135-140	0	0.0%
20-25	174.2	6.7%	80-85	39.5	1.5%	140-145	0	0.0%
25-30	200.0	7.6%	85-90	7.6	0.3%	145-150	0	0.0%
30-35	218.6	8.4%	90-95	0	0.0%	150-155	0	0.0%
35-40	230.1	8.8%	95-100	0	0.0%	155-160	0	0.0%
40-45	234.6	9.0%	100-105	0	0.0%	160-165	0	0.0%
45-50	231.0	8.8%	105-110	0	0.0%	165-170	0	0.0%
50-55	220.4	8.4%	110-115	0	0.0%	170-175	0	0.0%
55-60	202.9	7.8%	115-120	0	0.0%	175-180	0	0.0%

Zone	Lumens	% of Luminaire
0-40	1158	44.3%
0-60	2047	78.3%
0-90	2615	100.0%
90-180	0	0.0%

Candela Tabulation
Horizontal Angle (Degrees)

Vertical Angle (Degrees)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5
	0	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8	917.8
	5	911.3	914.7	912.3	915.2	916.2	914.7	911.6	913.7	908.3	913.7	911.6	914.7	916.2	915.2	912.3
	10	893.9	901.0	901.0	906.2	906.6	904.6	900.2	900.2	892.1	900.2	900.2	904.6	906.6	906.2	901.0
	15	871.4	877.6	878.7	888.7	889.3	885.1	875.5	873.7	865.3	873.7	875.5	885.1	889.3	888.7	878.7
	20	837.0	845.7	849.1	862.0	860.4	859.5	845.5	844.7	831.3	844.7	845.5	859.5	860.4	862.0	849.1
	25	795.9	803.1	811.6	825.7	830.5	822.9	809.4	801.0	788.5	801.0	809.4	822.9	830.5	825.7	811.6
	30	748.0	753.6	767.8	786.6	791.1	784.5	766.0	753.5	737.5	753.5	766.0	784.5	791.1	786.6	767.8
	35	691.6	700.2	717.8	739.3	746.4	736.3	714.7	696.2	680.9	696.2	714.7	736.3	746.4	739.3	717.8
	40	632.9	643.8	664.1	688.2	696.8	685.5	663.2	640.1	623.3	640.1	663.2	685.5	696.8	688.2	664.1
	45	565.8	579.4	604.2	634.6	644.8	632.2	601.9	573.5	557.3	573.5	601.9	632.2	644.8	634.6	604.2
	50	498.5	510.8	541.9	574.6	584.6	572.6	537.7	506.3	489.6	506.3	537.7	572.6	584.6	574.6	541.9
	55	428.5	442.0	476.2	510.1	520.0	508.2	472.1	436.7	418.9	436.7	472.1	508.2	520.0	510.1	476.2
	60	357.7	372.9	410.2	440.4	448.8	438.0	405.0	366.4	349.0	366.4	405.0	438.0	448.8	440.4	410.2
	65	288.7	303.5	341.0	366.2	369.3	362.8	335.5	297.3	278.8	297.3	335.5	362.8	369.3	366.2	341.0
	70	218.6	236.6	270.4	283.5	281.0	280.6	264.8	230.4	209.4	230.4	264.8	280.6	281.0	283.5	270.4
	75	151.1	171.1	196.5	195.9	190.7	194.0	190.7	165.2	143.8	165.2	190.7	194.0	190.7	195.9	196.5
	80	91.0	108.5	120.3	111.6	105.0	109.7	115.3	103.1	85.3	103.1	115.3	109.7	105.0	111.6	120.3
	85	39.2	48.6	43.9	33.9	29.6	32.5	40.3	44.0	35.9	44.0	40.3	32.5	29.6	33.9	43.9
	90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	95	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	105	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	110	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	115	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	120	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	125	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	130	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	135	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	140	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	145	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	150	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	155	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	160	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	165	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	170	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	175	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
	180	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Average Luminance (cd/m²)
Horizontal Angle (Degrees)


Vertical Angle (Degrees)	0	45	90
	0	2752	2752
	45	2399	2734
	55	2240	2718
	65	2048	2620
	75	1751	2209
	85	1350	1019



Coefficients of Utilization - Zonal Cavity Method


Effective Floor Cavity Reflectance 20%																		
Ceiling Cavity Reflectance	80				70				50			30			10			0
Wall Reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Room Cavity Ratio (RCR)	** Values are expressed as percent of total lumen output delivered to the task surface **																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	99	96	106	102	98	94	97	94	91	93	91	88	90	88	86	84
2	99	90	83	78	96	88	82	77	85	79	75	82	77	73	79	75	71	69
3	90	79	71	64	87	78	70	64	75	68	63	72	66	61	69	64	60	58
4	82	70	61	54	80	69	60	54	66	59	53	64	58	53	62	56	52	50
5	76	63	53	47	73	61	53	46	59	52	46	57	51	45	55	50	45	43
6	70	56	47	41	68	55	47	41	54	46	40	52	45	40	50	44	39	37
7	65	51	42	36	63	50	42	36	49	41	36	47	40	35	46	40	35	33
8	60	47	38	32	59	46	38	32	44	37	32	43	36	32	42	36	31	29
9	56	43	34	29	55	42	34	29	41	34	29	40	33	28	39	33	28	26
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	26	24

Beam and Field Information	
CIE Type:	Direct
Center Beam Intensity:	917.8 Candela
Central Cone Intensity:	916 Candela
Beam Flux:	1895.6 Lumens
Beam Angle (0-180):	105.1 Degrees
Beam Angle (90-270):	118.6 Degrees
Field Angle (0-180):	159.3 Degrees
Field Angle (90-270):	161.7 Degrees




ISOFootcandle Plot

Mounting Height - 8 Feet




Grid Lines in Units of Mounting Height



ANSI/IES TM-30-18 Color Rendition Report

Date:	2024-02-26	Manufacturer:	H E Williams Inc
Model:	FT-14-2-8-3500K-AF-DIM-UNC (FT-14-LS-8CS-AF-DIM-UNV)		



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4059
 y 0.3905
 u' 0.2362
 v' 0.5112

CIE 13.3-1995
(CRI)
 R_a 81
 R_g -1

Colors are for visual orientation purposes only. Created with the IES TM-30-18 Calculator Version 2.00.