

IES INDOOR REPORT

PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] GEN FROM 13257153.03
[TESTLAB] UL Verification Services Inc.
[ISSUE DATE] 2025-05-20
[MANUFAC] WILLIAMS INDOOR
[OTHER] H.E. WILLIAMS, INC. - CARTHAGE, MO.
[LUMCAT] V2DR-L8-940-DIM-UNV-RW-OF-WH_
[LUMINAIRE] Aluminum housing, optics, and trim enclosure
[LAMP] One white LED
[OTHER] This test was performed using the calibrated photodetector method of absolute photometry.
[SEARCH_SOURCETYPE] LED
[SEARCH_APPLICATION] Indoor, Downlight
[SEARCH_MOUNTING] Recessed

CHARACTERISTICS

| | |
|---------------------------------|--------------------|
| Lumens Per Lamp | N.A. (absolute) |
| Total Lamp Lumens | N.A. (absolute) |
| Luminaire Lumens | 670 |
| Total Luminaire Efficiency | N.A. |
| Luminaire Efficacy Rating (LER) | 63 |
| Total Luminaire Watts | 10.7 |
| Ballast Factor | 1.00 |
| CIE Type | Direct |
| Spacing Criterion (0-180) | 0.88 |
| Spacing Criterion (90-270) | 0.88 |
| Spacing Criterion (Diagonal) | 0.80 |
| Basic Luminous Shape | Circular |
| Luminous Length (0-180) | 0.21 ft (Diameter) |
| Luminous Width (90-270) | 0.21 ft (Diameter) |
| Luminous Height | 0.00 ft |

LUMINANCE DATA (cd/sq.m)

| Angle In Degrees | Average 0-Deg | Average 45-Deg | Average 90-Deg |
|------------------|---------------|----------------|----------------|
| 45 | 24031 | 24031 | 24031 |
| 55 | 19016 | 19016 | 19016 |
| 65 | 14214 | 14214 | 14214 |
| 75 | 7402 | 7402 | 7402 |
| 85 | 4485 | 4485 | 4485 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION

| | <u>0</u> |
|------|----------|
| 0.0 | 798.784 |
| 0.5 | 798.784 |
| 1.0 | 798.373 |
| 1.5 | 797.961 |
| 2.0 | 797.961 |
| 2.5 | 797.137 |
| 3.0 | 795.902 |
| 3.5 | 794.255 |
| 4.0 | 792.608 |
| 4.5 | 790.961 |
| 5.0 | 788.491 |
| 5.5 | 786.432 |
| 6.0 | 783.962 |
| 6.5 | 781.079 |
| 7.0 | 778.197 |
| 7.5 | 775.315 |
| 8.0 | 772.433 |
| 8.5 | 769.139 |
| 9.0 | 765.433 |
| 9.5 | 762.139 |
| 10.0 | 758.433 |
| 10.5 | 754.316 |
| 11.0 | 749.787 |
| 11.5 | 745.258 |
| 12.0 | 740.317 |
| 12.5 | 735.376 |
| 13.0 | 730.023 |
| 13.5 | 724.259 |
| 14.0 | 718.082 |
| 14.5 | 711.906 |
| 15.0 | 704.907 |
| 15.5 | 697.907 |
| 16.0 | 690.084 |
| 16.5 | 682.261 |
| 17.0 | 674.026 |
| 17.5 | 665.379 |
| 18.0 | 656.321 |
| 18.5 | 646.439 |
| 19.0 | 636.145 |
| 19.5 | 625.028 |
| 20.0 | 613.499 |
| 20.5 | 601.559 |
| 21.0 | 588.795 |
| 21.5 | 575.619 |
| 22.0 | 561.208 |
| 22.5 | 546.797 |
| 23.0 | 531.562 |
| 23.5 | 515.916 |
| 24.0 | 499.446 |
| 24.5 | 482.976 |
| 25.0 | 466.095 |
| 25.5 | 448.390 |
| 26.0 | 430.273 |
| 26.5 | 412.156 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION - (Cont.)

| | |
|------|---------|
| 27.0 | 394.163 |
| 27.5 | 376.087 |
| 28.0 | 357.847 |
| 28.5 | 339.689 |
| 29.0 | 321.120 |
| 29.5 | 302.426 |
| 30.0 | 283.898 |
| 30.5 | 265.658 |
| 31.0 | 247.664 |
| 31.5 | 230.289 |
| 32.0 | 213.572 |
| 32.5 | 197.761 |
| 33.0 | 183.103 |
| 33.5 | 169.515 |
| 34.0 | 156.875 |
| 34.5 | 145.305 |
| 35.0 | 134.805 |
| 35.5 | 125.170 |
| 36.0 | 116.441 |
| 36.5 | 108.618 |
| 37.0 | 101.660 |
| 37.5 | 95.442 |
| 38.0 | 89.801 |
| 38.5 | 84.778 |
| 39.0 | 80.373 |
| 39.5 | 76.502 |
| 40.0 | 73.043 |
| 40.5 | 70.038 |
| 41.0 | 67.361 |
| 41.5 | 64.973 |
| 42.0 | 62.832 |
| 42.5 | 60.938 |
| 43.0 | 59.209 |
| 43.5 | 57.685 |
| 44.0 | 56.244 |
| 44.5 | 54.927 |
| 45.0 | 53.691 |
| 45.5 | 52.497 |
| 46.0 | 51.386 |
| 46.5 | 50.274 |
| 47.0 | 49.245 |
| 47.5 | 48.215 |
| 48.0 | 47.186 |
| 48.5 | 46.198 |
| 49.0 | 45.210 |
| 49.5 | 44.221 |
| 50.0 | 43.274 |
| 50.5 | 42.369 |
| 51.0 | 41.421 |
| 51.5 | 40.516 |
| 52.0 | 39.651 |
| 52.5 | 38.745 |
| 53.0 | 37.880 |
| 53.5 | 37.016 |
| 54.0 | 36.151 |
| 54.5 | 35.287 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION - (Cont.)

| | |
|------|--------|
| 55.0 | 34.463 |
| 55.5 | 33.640 |
| 56.0 | 32.816 |
| 56.5 | 31.993 |
| 57.0 | 31.169 |
| 57.5 | 30.387 |
| 58.0 | 29.563 |
| 58.5 | 28.781 |
| 59.0 | 27.999 |
| 59.5 | 27.257 |
| 60.0 | 26.475 |
| 60.5 | 25.693 |
| 61.0 | 24.911 |
| 61.5 | 24.169 |
| 62.0 | 23.387 |
| 62.5 | 22.646 |
| 63.0 | 21.905 |
| 63.5 | 21.164 |
| 64.0 | 20.423 |
| 64.5 | 19.681 |
| 65.0 | 18.981 |
| 65.5 | 18.281 |
| 66.0 | 17.581 |
| 66.5 | 16.840 |
| 67.0 | 16.182 |
| 67.5 | 15.523 |
| 68.0 | 14.823 |
| 68.5 | 14.164 |
| 69.0 | 13.505 |
| 69.5 | 12.846 |
| 70.0 | 12.229 |
| 70.5 | 11.570 |
| 71.0 | 10.952 |
| 71.5 | 10.294 |
| 72.0 | 9.676 |
| 72.5 | 9.058 |
| 73.0 | 8.441 |
| 73.5 | 7.823 |
| 74.0 | 7.247 |
| 74.5 | 6.629 |
| 75.0 | 6.053 |
| 75.5 | 5.517 |
| 76.0 | 4.982 |
| 76.5 | 4.570 |
| 77.0 | 4.200 |
| 77.5 | 3.870 |
| 78.0 | 3.623 |
| 78.5 | 3.417 |
| 79.0 | 3.253 |
| 79.5 | 3.088 |
| 80.0 | 2.882 |
| 80.5 | 2.718 |
| 81.0 | 2.553 |
| 81.5 | 2.388 |
| 82.0 | 2.182 |
| 82.5 | 2.018 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION - (Cont.)

| | |
|-------|-------|
| 83.0 | 1.894 |
| 83.5 | 1.729 |
| 84.0 | 1.565 |
| 84.5 | 1.400 |
| 85.0 | 1.235 |
| 85.5 | 1.112 |
| 86.0 | 0.947 |
| 86.5 | 0.823 |
| 87.0 | 0.659 |
| 87.5 | 0.535 |
| 88.0 | 0.412 |
| 88.5 | 0.288 |
| 89.0 | 0.165 |
| 89.5 | 0.124 |
| 90.0 | 0.000 |
| 90.5 | 0.000 |
| 91.0 | 0.000 |
| 91.5 | 0.000 |
| 92.0 | 0.000 |
| 92.5 | 0.000 |
| 93.0 | 0.000 |
| 93.5 | 0.000 |
| 94.0 | 0.000 |
| 94.5 | 0.000 |
| 95.0 | 0.000 |
| 95.5 | 0.000 |
| 96.0 | 0.000 |
| 96.5 | 0.000 |
| 97.0 | 0.000 |
| 97.5 | 0.000 |
| 98.0 | 0.000 |
| 98.5 | 0.000 |
| 99.0 | 0.000 |
| 99.5 | 0.000 |
| 100.0 | 0.000 |
| 100.5 | 0.000 |
| 101.0 | 0.000 |
| 101.5 | 0.000 |
| 102.0 | 0.000 |
| 102.5 | 0.000 |
| 103.0 | 0.000 |
| 103.5 | 0.000 |
| 104.0 | 0.000 |
| 104.5 | 0.000 |
| 105.0 | 0.000 |
| 105.5 | 0.000 |
| 106.0 | 0.000 |
| 106.5 | 0.000 |
| 107.0 | 0.000 |
| 107.5 | 0.000 |
| 108.0 | 0.000 |
| 108.5 | 0.000 |
| 109.0 | 0.000 |
| 109.5 | 0.000 |
| 110.0 | 0.000 |
| 110.5 | 0.000 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION - (Cont.)

| | |
|-------|-------|
| 111.0 | 0.000 |
| 111.5 | 0.000 |
| 112.0 | 0.000 |
| 112.5 | 0.000 |
| 113.0 | 0.000 |
| 113.5 | 0.000 |
| 114.0 | 0.000 |
| 114.5 | 0.000 |
| 115.0 | 0.000 |
| 115.5 | 0.000 |
| 116.0 | 0.000 |
| 116.5 | 0.000 |
| 117.0 | 0.000 |
| 117.5 | 0.000 |
| 118.0 | 0.000 |
| 118.5 | 0.000 |
| 119.0 | 0.000 |
| 119.5 | 0.000 |
| 120.0 | 0.000 |
| 120.5 | 0.000 |
| 121.0 | 0.000 |
| 121.5 | 0.000 |
| 122.0 | 0.000 |
| 122.5 | 0.000 |
| 123.0 | 0.000 |
| 123.5 | 0.000 |
| 124.0 | 0.000 |
| 124.5 | 0.000 |
| 125.0 | 0.000 |
| 125.5 | 0.000 |
| 126.0 | 0.000 |
| 126.5 | 0.000 |
| 127.0 | 0.000 |
| 127.5 | 0.000 |
| 128.0 | 0.000 |
| 128.5 | 0.000 |
| 129.0 | 0.000 |
| 129.5 | 0.000 |
| 130.0 | 0.000 |
| 130.5 | 0.000 |
| 131.0 | 0.000 |
| 131.5 | 0.000 |
| 132.0 | 0.000 |
| 132.5 | 0.000 |
| 133.0 | 0.000 |
| 133.5 | 0.000 |
| 134.0 | 0.000 |
| 134.5 | 0.000 |
| 135.0 | 0.000 |
| 135.5 | 0.000 |
| 136.0 | 0.000 |
| 136.5 | 0.000 |
| 137.0 | 0.000 |
| 137.5 | 0.000 |
| 138.0 | 0.000 |
| 138.5 | 0.000 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION - (Cont.)

| | |
|-------|-------|
| 139.0 | 0.000 |
| 139.5 | 0.000 |
| 140.0 | 0.000 |
| 140.5 | 0.000 |
| 141.0 | 0.000 |
| 141.5 | 0.000 |
| 142.0 | 0.000 |
| 142.5 | 0.000 |
| 143.0 | 0.000 |
| 143.5 | 0.000 |
| 144.0 | 0.000 |
| 144.5 | 0.000 |
| 145.0 | 0.000 |
| 145.5 | 0.000 |
| 146.0 | 0.000 |
| 146.5 | 0.000 |
| 147.0 | 0.000 |
| 147.5 | 0.000 |
| 148.0 | 0.000 |
| 148.5 | 0.000 |
| 149.0 | 0.000 |
| 149.5 | 0.000 |
| 150.0 | 0.000 |
| 150.5 | 0.000 |
| 151.0 | 0.000 |
| 151.5 | 0.000 |
| 152.0 | 0.000 |
| 152.5 | 0.000 |
| 153.0 | 0.000 |
| 153.5 | 0.000 |
| 154.0 | 0.000 |
| 154.5 | 0.000 |
| 155.0 | 0.000 |
| 155.5 | 0.000 |
| 156.0 | 0.000 |
| 156.5 | 0.000 |
| 157.0 | 0.000 |
| 157.5 | 0.000 |
| 158.0 | 0.000 |
| 158.5 | 0.000 |
| 159.0 | 0.000 |
| 159.5 | 0.000 |
| 160.0 | 0.000 |
| 160.5 | 0.000 |
| 161.0 | 0.000 |
| 161.5 | 0.000 |
| 162.0 | 0.000 |
| 162.5 | 0.000 |
| 163.0 | 0.000 |
| 163.5 | 0.000 |
| 164.0 | 0.000 |
| 164.5 | 0.000 |
| 165.0 | 0.000 |
| 165.5 | 0.000 |
| 166.0 | 0.000 |
| 166.5 | 0.000 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

CANDELA TABULATION - (Cont.)

| | |
|-------|-------|
| 167.0 | 0.000 |
| 167.5 | 0.000 |
| 168.0 | 0.000 |
| 168.5 | 0.000 |
| 169.0 | 0.000 |
| 169.5 | 0.000 |
| 170.0 | 0.000 |
| 170.5 | 0.000 |
| 171.0 | 0.000 |
| 171.5 | 0.000 |
| 172.0 | 0.000 |
| 172.5 | 0.000 |
| 173.0 | 0.000 |
| 173.5 | 0.000 |
| 174.0 | 0.000 |
| 174.5 | 0.000 |
| 175.0 | 0.000 |
| 175.5 | 0.000 |
| 176.0 | 0.000 |
| 176.5 | 0.000 |
| 177.0 | 0.000 |
| 177.5 | 0.000 |
| 178.0 | 0.000 |
| 178.5 | 0.000 |
| 179.0 | 0.000 |
| 179.5 | 0.000 |
| 180.0 | 0.000 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

ZONAL LUMEN SUMMARY

| Zone | Lumens | %Lamp | %Fixt |
|---------|--------|-------|--------|
| 0-20 | 270.17 | N.A. | 40.30 |
| 0-30 | 478.28 | N.A. | 71.40 |
| 0-40 | 569.84 | N.A. | 85.00 |
| 0-60 | 643.03 | N.A. | 95.90 |
| 0-80 | 668.83 | N.A. | 99.80 |
| 0-90 | 670.26 | N.A. | 100.00 |
| 10-90 | 595.96 | N.A. | 88.90 |
| 20-40 | 299.67 | N.A. | 44.70 |
| 20-50 | 341.97 | N.A. | 51.00 |
| 40-70 | 92.06 | N.A. | 13.70 |
| 60-80 | 25.80 | N.A. | 3.80 |
| 70-80 | 6.93 | N.A. | 1.00 |
| 80-90 | 1.42 | N.A. | 0.20 |
| 90-110 | 0.00 | N.A. | 0.00 |
| 90-120 | 0.00 | N.A. | 0.00 |
| 90-130 | 0.00 | N.A. | 0.00 |
| 90-150 | 0.00 | N.A. | 0.00 |
| 90-180 | 0.00 | N.A. | 0.00 |
| 110-180 | 0.00 | N.A. | 0.00 |
| 0-180 | 670.26 | N.A. | 100.00 |

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

| Zone | Lumens |
|---------|--------|
| 0-10 | 74.30 |
| 10-20 | 195.87 |
| 20-30 | 208.10 |
| 30-40 | 91.57 |
| 40-50 | 42.30 |
| 50-60 | 30.89 |
| 60-70 | 18.87 |
| 70-80 | 6.93 |
| 80-90 | 1.42 |
| 90-100 | 0.00 |
| 100-110 | 0.00 |
| 110-120 | 0.00 |
| 120-130 | 0.00 |
| 130-140 | 0.00 |
| 140-150 | 0.00 |
| 150-160 | 0.00 |
| 160-170 | 0.00 |
| 170-180 | 0.00 |

IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

| RC | 80 | | | | 70 | | | | 50 | | | 30 | | | 10 | | | 0 |
|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1 | 113 | 110 | 107 | 105 | 111 | 108 | 105 | 103 | 104 | 102 | 100 | 100 | 98 | 97 | 97 | 95 | 94 | 92 |
| 2 | 107 | 102 | 97 | 94 | 105 | 100 | 96 | 93 | 97 | 93 | 91 | 94 | 91 | 89 | 91 | 89 | 87 | 85 |
| 3 | 101 | 94 | 89 | 85 | 99 | 93 | 88 | 84 | 90 | 86 | 83 | 88 | 84 | 81 | 86 | 83 | 80 | 79 |
| 4 | 96 | 88 | 82 | 78 | 94 | 87 | 81 | 77 | 85 | 80 | 76 | 83 | 79 | 75 | 81 | 77 | 74 | 73 |
| 5 | 91 | 82 | 76 | 72 | 89 | 81 | 75 | 71 | 79 | 74 | 71 | 78 | 73 | 70 | 76 | 72 | 69 | 68 |
| 6 | 86 | 77 | 71 | 66 | 85 | 76 | 70 | 66 | 75 | 70 | 66 | 73 | 69 | 65 | 72 | 68 | 65 | 63 |
| 7 | 82 | 73 | 66 | 62 | 81 | 72 | 66 | 62 | 71 | 65 | 61 | 69 | 65 | 61 | 68 | 64 | 61 | 59 |
| 8 | 78 | 68 | 62 | 58 | 77 | 68 | 62 | 58 | 67 | 61 | 58 | 66 | 61 | 57 | 65 | 60 | 57 | 56 |
| 9 | 75 | 65 | 59 | 55 | 73 | 64 | 58 | 55 | 63 | 58 | 54 | 62 | 58 | 54 | 62 | 57 | 54 | 53 |
| 10 | 71 | 61 | 55 | 52 | 70 | 61 | 55 | 51 | 60 | 55 | 51 | 59 | 55 | 51 | 59 | 54 | 51 | 50 |


IES INDOOR REPORT
PHOTOMETRIC FILENAME : V2DR-L8-940-DIM-UNV-RW-OF-WH_.IES

UGR TABLE - CORRECTED

| | | | | | | | | | | | |
|----------------|------|----------------------|------|------|------|------|--------------------|------|------|------|------|
| Reflectances | | | | | | | | | | | |
| Ceiling Cavity | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 | |
| Walls | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 | |
| Floor Cavity | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | |
| Room Size | | UGR Viewed Crosswise | | | | | UGR Viewed Endwise | | | | |
| X=2H | Y=2H | 17.5 | 18.6 | 17.9 | 18.9 | 19.2 | 17.5 | 18.6 | 17.9 | 18.9 | 19.2 |
| | 3H | 18.5 | 19.5 | 18.9 | 19.8 | 20.2 | 18.5 | 19.5 | 18.9 | 19.8 | 20.2 |
| | 4H | 18.7 | 19.6 | 19.1 | 20.0 | 20.4 | 18.7 | 19.6 | 19.1 | 20.0 | 20.4 |
| | 6H | 18.7 | 19.6 | 19.2 | 20.0 | 20.3 | 18.7 | 19.6 | 19.2 | 20.0 | 20.3 |
| | 8H | 18.7 | 19.5 | 19.2 | 19.9 | 20.3 | 18.7 | 19.5 | 19.2 | 19.9 | 20.3 |
| | 12H | 18.7 | 19.5 | 19.2 | 19.9 | 20.3 | 18.7 | 19.5 | 19.2 | 19.9 | 20.3 |
| 4H | 2H | 17.8 | 18.7 | 18.2 | 19.1 | 19.5 | 17.8 | 18.7 | 18.2 | 19.1 | 19.5 |
| | 3H | 19.0 | 19.7 | 19.4 | 20.2 | 20.6 | 19.0 | 19.7 | 19.4 | 20.2 | 20.6 |
| | 4H | 19.2 | 19.9 | 19.7 | 20.3 | 20.8 | 19.2 | 19.9 | 19.7 | 20.3 | 20.8 |
| | 6H | 19.3 | 19.9 | 19.8 | 20.3 | 20.8 | 19.3 | 19.9 | 19.8 | 20.3 | 20.8 |
| | 8H | 19.3 | 19.8 | 19.8 | 20.3 | 20.8 | 19.3 | 19.8 | 19.8 | 20.3 | 20.8 |
| | 12H | 19.3 | 19.8 | 19.8 | 20.3 | 20.7 | 19.3 | 19.8 | 19.8 | 20.3 | 20.7 |
| 8H | 4H | 19.2 | 19.8 | 19.7 | 20.2 | 20.7 | 19.2 | 19.8 | 19.7 | 20.2 | 20.7 |
| | 6H | 19.4 | 19.8 | 19.9 | 20.3 | 20.8 | 19.4 | 19.8 | 19.9 | 20.3 | 20.8 |
| | 8H | 19.4 | 19.8 | 19.9 | 20.3 | 20.8 | 19.4 | 19.8 | 19.9 | 20.3 | 20.8 |
| | 12H | 19.4 | 19.7 | 19.9 | 20.2 | 20.8 | 19.4 | 19.7 | 19.9 | 20.2 | 20.8 |
| 12H | 4H | 19.2 | 19.6 | 19.7 | 20.1 | 20.6 | 19.2 | 19.6 | 19.7 | 20.1 | 20.6 |
| | 6H | 19.3 | 19.7 | 19.9 | 20.2 | 20.7 | 19.3 | 19.7 | 19.9 | 20.2 | 20.7 |
| | 8H | 19.4 | 19.7 | 19.9 | 20.2 | 20.8 | 19.4 | 19.7 | 19.9 | 20.2 | 20.8 |

Maximum UGR = 20.8

POLAR GRAPH



Maximum Candela = 798.784 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)