




Shown with lamps, not included



CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- TLED fixtures provide on-site lamping flexibility and simple installation
- Hinging/locking lamp brackets and factory-mounted, prewired sockets reduce installation time
- Channel connector furnished for continuous row applications (included with 8' units only)
- Quarter-turn fastener secures wireway cover to housing
- Special reflectors are available for precise light distribution
- Available on QuickShip
- Made Right Here® in the USA

SPECIFICATIONS

- HOUSING – 22-gauge die-formed C.R.S.
- FINISH – 92% minimum average reflective white polyester powder coat bonded to phosphate-free, multi-stage pretreated metal. All parts painted after fabrication to facilitate installation, increase efficiency, and inhibit corrosion.
- ELECTRICAL – Prewired for Type B, single or double end, non-shunted LED tubes, lamps by others.
- MOUNTING – Surface (ceiling or wall) or suspended (hanging hardware required).
- LABELS – UL/CUL listed as LED surface luminaire suitable for dry or damp locations.
- WARRANTY – 5-year limited fixture warranty, see hew.com/warranty.

ORDERING EXAMPLE: 76 - 4 - 24T8LS/B - OPTIONS - UNV

ORDERING INFO

SERIES	NOMINAL LENGTH	TOTAL LAMPS	LAMP SIZE	WIRING	LAMP TYPE
76	4 4'	4' Fixtures	4T5L 4' T5 LED tube	S Single end	B Type B
	8 8'	1, 2, or 3 8' Fixtures	4T8L 4' T8 LED tube	D Double end	

OPTIONS ^[2]

WG-7611	11-gauge white powder coat wireguard
WG-7614	14-gauge white powder coat wireguard
VBY	(2) Y-hangers
VBY-2	(2) Y-hangers and (2) 2' chains
GC2/Y18/_	Cable suspension system ^[3]
GC2/L/10	10' cable suspension system with loop ^[4]
320	1-1/2" ceiling spacer
SHS	Surface mount hanger for NEMA-G T-bar system
GAT	T-bar fastener for 320 ceiling spacer
SS-12	Single stem and canopy, 12"
SWS-12	Swivel stem and canopy, 12"

VOLTAGE

UNV 120-277V

QUICKSHIP

4'	76-4-24T8LS/B-QS-UNV
8'	76-8-44T8LS/B-QS-UNV

NOTES


- 1, 2, or 3-lamp cross-section.
- See page 2 for SPECIAL REFLECTOR OPTIONS. See page 2 for FINISH OPTIONS. Custom colors available upon request. See Technical Info for Power Entry details. See page 2 for MOUNTING OPTIONS.

- 1 pair. Must specify length: 5', 10', 15', or 20'
- Requires VBY hanger.




76 TLED Standard Strip


FIXTURE DETAILS



MOUNTING OPTIONS




SPECIAL REFLECTOR OPTIONS



- Reflectors are ordered separately. Example: R1172-4-76 REFL. For additional styles, see [Technical Info](#).
- Clear polycarbonate reflector aligners for continuous row applications (8' unit only) are ordered with reflectors.
- Note: Drawings represent reflector style. Actual cross-section will vary depending on lamp configuration.

FINISH OPTIONS



For custom color, please specify RAL code or a manufacturer code with description. All custom colors other than RAL require two sample swatches, minimum 1" square.