



CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- Compact, low profile design
- UV stabilized, silk screened acrylic panels provide consistent, uniform illumination
- Available as full-time AC powered unit or emergency unit with battery backup
- EXIT or STAIR sign illumination
- EM unit provides 120 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs
- Fully automatic solid-state two rate charger on EM unit recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing

SPECIFICATIONS

- HOUSING – Premium-grade extruded aluminum.
- ELECTRICAL – Dual 120V/277 voltage standard. 4.8V long life, maintenance-free, rechargeable NiCd battery when specified with EM power option.
- MOUNTING – Cast aluminum mounting canopy for ceiling, side, or wall mount installation.
- LISTINGS –
 - UL 924 standard as an exit light suitable for dry or damp locations (0°C - +50°C).
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, local and state codes.
 - Meets City of Chicago requirements.
 - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty.

ORDERING EXAMPLE: EXIT/EL/CHICAGO - SF - WHT - AC - DA - D

ORDERING INFO

SERIES	NUMBER OF FACES	HOUSING COLOR	POWER OPTIONS
EXIT/EL/CHICAGO	SF Single face DF Double face	WHT Industry-standard white BA Brushed aluminum	AC AC operation EM AC operation with emergency battery backup

DIRECTIONAL ARROWS	VOLTAGE
EXIT SIGNAGE	D 120V/277V
NA No Arrows	
DA Double arrows	
LA Left arrows ^[1]	
RA Right arrows ^[2]	
LARA Left/Right arrow ^[3]	
STAIR SIGNAGE	
SWNA Stairs no arrow	
SWDA Stairs double arrows	
SWRA Stairs right arrow ^[4]	
SWLA Stairs left arrow ^[5]	
SWLARA Stairs left/right arrow ^[6]	

NOTES

- ¹ Single face only.
- ² Single face only.
- ³ Double face only.

- ⁴ Single face only.
- ⁵ Single face only.
- ⁶ Double face only.

FIXTURE DETAILS

DIRECTIONAL ARROWS

