

CATALOG #: \_\_\_\_\_

TYPE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

## FEATURES

- Spec-grade Exit sign with LED lamp heads in one low-profile housing with choice of three faceplate finishes
- Provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs in red or green
- Remote capable option available
- Fully automatic solid-state two rate charger recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Unique design allows double face conversion in the field
- Removable directional indicators
- Remote capacity available, see options

## SPECIFICATIONS

- HOUSING** – Premium-grade cast aluminum.
- ELECTRICAL** – Dual 120/277 voltage standard. 3W (1 LED x 3 watts) per head. 8.4V long life, maintenance-free, rechargeable NiCd battery. 3W remote capacity when specified with RC option.
- MOUNTING** – Aluminum mounting canopy for ceiling or side mount installation. Universal knockout pattern on back for wall mount.
- LISTINGS** –
  - UL 924 standard as an exit light suitable for dry or damp locations (0°C - +50°C).
  - Meets NFPA 101 Life Safety Code, NEC, OSHA, local and state codes.
  - Certified to CEC under Title 20 Regulations.
- WARRANTY** – 5-year limited warranty.

## ORDERING EXAMPLE: EXIT/EM/CA - R - WF - WHT - OPTIONS - D

### ORDERING INFO

SERIES	LETTER COLOR	FACEPLATE FINISH	HOUSING COLOR
EXIT/EM/CA	R Red	AF Brushed aluminum	WHT Industry-standard white
	G Green	BF Black	BLK Black
		WF Industry-standard white	BA Brushed aluminum

OPTIONS	VOLTAGE
RC Remote capable	D 120V/277V
PC2 Polycarbonate shield <sup>[1]</sup>	
WG Wireguard, white <sup>[2]</sup>	

### REMOTE HEADS: RHL - T - WHT - OPTIONS - MV <sup>[3]</sup>

SERIES	HOUSING	HOUSING COLOR	OPTIONS	VOLTAGE
RHL Single remote head	T Thermoplastic <sup>[4]</sup>	WHT Industry-standard white <sup>[7]</sup>	HL 1.5-watt remote head, 12 LEDs	MV Multi-voltage <sup>[9]</sup>
DRHL Dual remote head	D Die-cast <sup>[5]</sup>	BLK Black		
WETRHL Wet location single remote head	P Polycarbonate <sup>[6]</sup>	GRAY Gray <sup>[8]</sup>		
WETDRHL Wet location dual remote head				

## NOTES

- Wall mount only. Shipped separately. See page 2 for OPTIONS DETAILS.
- Wall mount only. Shipped separately. See page 2 for OPTIONS DETAILS.
- Optional. Ships separately. See page 2 for REMOTE HEAD DETAILS. Must specify RC option.
- RHL and DRHL only.

- WETRHL and WETDRHL only.
- WETRHL and WETDRHL only.
- RHL and DRHL only.
- WETRHL and WETDRHL only.
- For use with 3.6V, 6V, 9.6V, or 12V power source.


## ELECTRICAL INFORMATION

	INPUT WATTS (W)	INPUT AMPS (A)
120V	4.6	0.05
277V	4.8	0.02

## MOUNTING DETAILS

### WALL MOUNT BOLT CIRCLE PATTERN

Not to scale.



## REMOTE HEAD DETAILS

RHL



DIMENSIONS: 5-7/8" x 4-7/8"

DRHL



DIMENSIONS: 8-1/2" x 5"

WETRHL



DIMENSIONS: 4-1/2" x 6-5/8"

WETDRHL



DIMENSIONS: 10-3/8" x 6-3/4"

## OPTIONS DETAILS

Wall mount only. Ships separately.

PC2



DIMENSIONS: 15" x 22" x 7-3/4"

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"