



CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- Thin design for use in low-level applications
- 3.1 watts per light strip
- Patent-pending high performance, smooth, chrome plated, metalized reflector with acrylic UV stabilized lens for optical light distribution
- Ultra-bright, energy efficient, long life LEDs
- Message in red or green
- LED indicator alerts occupant on battery condition (Green = normal, Red = check battery)
- Charge rate/power on LED indicator and built-in test switch on emergency units
- 3.6V long-life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch for minimum 90 minutes of emergency operation
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Removable directional indicators

ORDERING EXAMPLE: EXIT/EM/LOW - R - WHT - D

ORDERING INFO

| SERIES | LETTER COLOR | HOUSING COLOR | VOLTAGE |
|-------------|------------------|------------------------------------------|----------------|
| EXIT/EM/LOW | R Red G Green | WHT Industry-standard white BLK Black | D 120V or 277V |

SPECIFICATIONS

- HOUSING – Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic
- ELECTRICAL – Universal voltage, 120 or 277 VAC operation.
- MOUNTING – Universal knockout pattern on back plate for wall mount.
- LISTINGS –
 - UL 924 standard as an exit light suitable for dry or damp locations (0°C – 50°C).
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, local and state codes.
 - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty, see hew.com/warranty.

MOUNTING DETAILS

WALL MOUNT BOLT CIRCLE PATTERN

