



CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- Spec-grade, low profile thin plastic design for use in low-level applications
- High performance, smooth, chrome-plated, metalized reflector with acrylic UV stabilized lens for optimal light distribution
- Provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs in red or green
- Fully automatic solid-state two rate charger recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Removable directional indicators

ORDERING EXAMPLE: EXIT/EM/LOW - R - WHT - D

ORDERING INFO

SERIES	LETTER COLOR	HOUSING COLOR	VOLTAGE
EXIT/EM/LOW	R Red G Green	WHT Industry-standard white BLK Black	D 20V/277V

SPECIFICATIONS

- HOUSING – Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic
- ELECTRICAL – Dual 120/277 voltage standard. 3.1 watts (24 LEDs x 0.13 watts) per light strip. 3.6V Long life, maintenance-free, rechargeable NiCd battery.
- MOUNTING – Universal knockout pattern on back plate for wall mount.
- LISTINGS –
 - UL 924 standard as an exit light suitable for dry or damp locations (0°C - +50°C).
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, local and state codes.
 - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty.

MOUNTING DETAILS

WALL MOUNT BOLT CIRCLE PATTERN

Not to scale.

