

CATALOG #: \_\_\_\_\_

Type: \_\_\_\_\_

PROJECT: \_\_\_\_\_



FEATURES

- NEMA 4X, NSF and IP66 certified for use in food service operations
- Corrosion-resistant enclosure and high-impact lens for tough environments
- Tamper-resistant hardware option for vandal-prone areas
- Ultra-bright, energy-efficient, long-life LEDs in red or green
- Available as full-time AC powered unit or emergency unit with battery backup
- Removable directional indicators
- EM unit provides 90 minutes of emergency operation
- Dual color LED indicator light alerts on battery condition
- Dual circuit option (AC-only) connects to two different supplies simultaneously
- Fully automatic solid-state two rate charger on EM units recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing
- Self-diagnostic option performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes

ORDERING EXAMPLE: EXIT/IP - SF - R - WHT - EM - OPTIONS - D

| SERIES  | NUMBER OF FACES                  | LETTER COLOR     | HOUSING COLOR                            | POWER OPTIONS                                                    |
|---------|----------------------------------|------------------|------------------------------------------|------------------------------------------------------------------|
| EXIT/IP | SF Single face<br>DF Double face | R Red<br>G Green | WHT Industry-standard white<br>BLK Black | AC AC operation<br>EM AC operation with emergency battery backup |

| OPTIONS                                 | VOLTAGE     |
|-----------------------------------------|-------------|
| TP Tamper-resistant                     | D 120V/277V |
| SDT Self-diagnostic test <sup>[1]</sup> | 120 120V    |
| DC Dual circuit <sup>[2]</sup>          | 277 277V    |
| WG Wireguard, white <sup>[3]</sup>      |             |

SPECIFICATIONS

- HOUSING – Reinforced polycarbonate construction in white or black finish. Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- ELECTRICAL – Dual 120/277 voltage. 4.8V long life, maintenance-free, rechargeable NiCd battery on EM model.
- MOUNTING – Polycarbonate mounting canopy included for top or end mount. Wall mount with universal knockout pattern and gasket for watertight seal on back. Knockouts provided for conduit feed applications.
- LISTINGS –
  - UL 924 standard as an exit light suitable for wet locations (-20°C - +50°C)
  - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
  - IP66 rated for ingress protection
  - NEMA 4X and NSF rated
  - Certified to CEC under Title 20 Regulations
- WARRANTY – 5-year limited warranty.

NOTES


- <sup>1</sup> EM Power Option only.  
<sup>2</sup> AC Power Option only. Must specify 120V or 277V.  
<sup>3</sup> Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.

ELECTRICAL INFORMATION

|       | INPUT WATTS (W) | INPUT AMPS (A) |       |
|-------|-----------------|----------------|-------|
|       | 120V/277V       | 120V           | 277V  |
| RED   | 2.5             | 0.025          | 0.010 |
| GREEN | 2.5             | 0.025          | 0.010 |

FIXTURE DETAILS

BACK MOUNT



WHITE HOUSING | GREEN LETTERS



BLACK HOUSING | RED LETTERS




BLACK HOUSING | GREEN LETTERS



OPTIONS DETAILS

Wall mount only. Ships separately.

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"