

CATALOG #: _____

Type: _____

PROJECT: _____

FEATURES

- New York City compliant 8" tall red letters
- Durable steel housing
- Available as full-time AC powered unit or emergency unit with battery backup
- EM unit provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs
- Fully automatic solid-state two rate charger on EM unit recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Unique design allows double face conversion in the field
- Removable directional indicators

ORDERING EXIT/NYC - EM - WHT - OPTIONS - D

ORDERING INFO

SERIES	POWER OPTIONS	HOUSING COLOR	OPTIONS ⁽¹⁾	VOLTAGE
EXIT/NYC	AC AC operation	BLK Black	PC2 Polycarbonate shield	D 120V/277V
	EM AC operation with emergency battery backup	WHT Industry-standard white	WG Wireguard, white	

SPECIFICATIONS

- HOUSING – Durable, powder-coated 20-gauge steel construction.
- ELECTRICAL – Dual 120/277 voltage standard. 3.6V long life, maintenance-free, rechargeable NiCd battery when specified with EM power option.
- MOUNTING – Aluminum mounting canopy included for top or end mount. Universal knockout pattern on back plate for wall mount. Knockout provided for conduit feed applications.
- LISTINGS –
 - UL 924 standard as an exit light suitable for dry or damp locations.
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
 - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty.

NOTES

¹ Ships separately. See page 2 for OPTIONS DETAILS.

OPTIONS DETAILS


Ships separately.

PC2



DIMENSIONS: 15" x 22" x 7-3/4"

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"