

CATALOG #: _____

Type: _____

PROJECT: _____



FEATURES

- Selectable red or green LEDs on-site with a built-in switch
- Compact, low-profile design
- EM unit provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs
- Fully automatic solid-state two rate charger on EM units recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Unique design allows double face conversion in the field
- Removable directional indicators
- Available on QuickShip

ORDERING EXAMPLE: EXIT - RG - EM - WHT - OPTIONS - D

ORDERING INFO

SERIES	LETTER COLOR	POWER OPTIONS	HOUSING COLOR
EXIT	RG Field-selectable red or green	EM AC operation with emergency battery backup	WHT Industry-standard white

OPTIONS	VOLTAGE
PC1 Polycarbonate shield ^[1]	D 120V/277V
WG Wireguard, white ^[2]	

QUICKSHIP

EXIT-RG-EM-WHT-QS-D

SPECIFICATIONS

- HOUSING – Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white finish.
- ELECTRICAL – Dual 120/277 voltage standard. 1.2V long life, maintenance-free, rechargeable NiCd battery when specified with EM power option.
- MOUNTING – Mounting canopy for top or end mount. Universal knockout pattern on back plate for wall mount.
- LISTINGS –
 - UL924 standard as an exit light suitable for dry or damp locations (0°C to 50°C).
 - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
 - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty.

NOTES

- ¹ Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.
- ² Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.

ELECTRICAL INFORMATION

	INPUT WATTS (W)	INPUT AMPS (A)
120V	1.0	0.1
277V	1.0	0.1

OPTIONS DETAILS


Wall mount only. Ships separately.

PC1



DIMENSIONS: 13-3/16" x 9-3/16" x 2-1/2"

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"