

CATALOG #: \_\_\_\_\_

Type: \_\_\_\_\_

PROJECT: \_\_\_\_\_

**FEATURES**

- Compact, low-profile design
- Provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs in red or green
- Fully automatic solid-state two rate charger on EM units recharges battery in 24 hours
- Charge rate/power “ON” LED indicator light and push-to-test switch for mandated code compliance testing
- Unique design allows double face conversion in the field
- Removable directional indicators
- Custom message available
- Self-diagnostic option performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes

**ORDERING EXAMPLE: EXIT - R - EM - WHT - OPTIONS - D**

**ORDERING INFO**

SERIES	LETTER COLOR	POWER OPTIONS	HOUSING COLOR
EXIT	R Red G Green	EM AC operation with emergency battery backup	WHT Industry-standard white BLK Black

OPTIONS	VOLTAGE
COPY/SF Custom message, single face <sup>[1]</sup>	D 120V/277V
COPY/DF Custom message, double face <sup>[2]</sup>	
SALIDA Salida faceplate <sup>[3]</sup>	
SDT Self-diagnostic test	
PC1 Polycarbonate shield <sup>[4]</sup>	
WG Wireguard, white <sup>[5]</sup>	

**SPECIFICATIONS**

- HOUSING – Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- ELECTRICAL – Dual 120/277 voltage. 1.2V Long life, maintenance-free, rechargeable NiCd battery.
- MOUNTING – Mounting canopy for top or end mount. Universal knockout pattern on back plate for wall mount.
- LISTINGS –
  - UL 924 standard as an exit light suitable for dry or damp locations (0°C - +50°C).
  - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
  - Certified to CEC under Title 20 Regulations.
- WARRANTY – 5-year limited warranty.

**NOTES**

- <sup>1</sup> Consult factory.  
<sup>2</sup> Consult factory.  
<sup>3</sup> Industry-standard white only.

- <sup>4</sup> Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.  
<sup>5</sup> Wall mount only. Ships separately. See page 2 for OPTIONS DETAILS.


ELECTRICAL INFORMATION

	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
RED	2.5	2.5	0.05	0.05
GREEN	2.7	2.7	0.05	0.05

OPTIONS DETAILS


Wall mount only. Ships separately.

PC1



DIMENSIONS: 13-3/16" x 9-3/16" x 2-1/2"

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"