

2x2 | 2x4
Shown with RA lens

CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- Easily change the color temperature on-site with fieldseleCCT[®] technology
- Three switchable CCT settings provide ultimate flexibility – 3000K, 3500K and 4000K
- Room-side access
- Ultra slim 2-3/8" for minimal plenum space
- Uniform ambient illumination
- Companion surface and retrofit kit preserve continuity, see hew.com
- Maximize energy savings with efficacies up to 123 lm/W
- Rated for direct contact with insulation
- Heavy duty C.R.S. construction
- Made Right Here[®] in the USA

SPECIFICATIONS

- HOUSING/REFLECTOR – Precision die-formed 22-gauge C.R.S.
- SHIELDING – Diffuse ribbed acrylic.
- FINISH – Highly reflective non-glare matte white polyester powder coat bonded to phosphate-free, multi-stage pretreated metal. All parts painted after fabrication to facilitate installation, increase efficiency, and inhibit corrosion.
- ELECTRICAL – High quality mid-power LED boards with switchable CCT – 3000K, 3500K, and 4000K. L70 >50,000 hours. fieldseleCCT[®] products use LEDs of multiple CCTs and may produce a perceptibly different shade of white from single-CCT products at the same CCT. All CCTs are within 3 MacAdams ellipses.
- MOUNTING – Designed for NEMA Type “G” 1” grid ceiling standard. For NEMA Type “NFG” and “SG” 9/16” grid installations, specify EQCLIPS option. Drywall kit accessories available, ordered separately.
- LISTINGS –
 - cCSAus certified as luminaire suitable for dry or damp locations.
 - IC-rated for direct contact with insulation.
 - City of Chicago Environmental Air approved when specified with CP option.
- WARRANTY – 5-year limited warranty, see hew.com/warranty.

ORDERING EXAMPLE: PT - 2 4 - L62/8FS - RA - OPTIONS - DIM - UNV

ORDERING INFO

SERIES	WIDTH	LENGTH	LUMENS ^[1]	CRI	CCT	SHIELDING
PT	1 1' ^[2]	2 2' ^[3]	1x4	80	FS fieldseleCCT 3000K, 3500K, 4000K ^[4]	RA Diffuse ribbed acrylic, round SA Diffuse ribbed acrylic, square ^[5]
			L25 2,500lm			
			L37 3,700lm			
	2 2'	4 4'	L50 5,000lm			
			2x2			
			L24 2,400lm			
	2 2'	4 4'	L36 3,600lm			
			2x4			
			L37 3,700lm			
	2 2'	4 4'	L55 5,500lm			
			L62 6,200lm			

OPTIONS ^[6]	CONTROL ^[7]	VOLTAGE
EM/7W 7-watt emergency LED battery ^[8]	DIM Dimming driver	120 120V
EM/7WRM Remote mount 7-watt emergency battery ^[9]	DRV Non-dimming driver	277 277V
EM/10W 10-watt emergency battery ^[10]	VDO/DSR Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC) and sensor-ready driver ^[14]	UNV 120-277V
EM/10WLP Low-profile 10-watt emergency battery ^[11]	VRF/DSR Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF) and sensor-ready driver ^[15]	347 347V ^[16]
EM/12W 12-watt emergency battery ^[12]		
EQCLIPS Earthquake clips ^[13]		
AMW Anti-microbial white finish		
CP Chicago Plenum (CCEA)		
DFK-1248W Drywall kit, 12" x 48", white		
DFK-2424W Drywall kit, 24" x 24", white		
DFK-2448W Drywall kit, 24" x 48", white		

QUICKSHIP

2x2	2x4
PT-22-L36/8FS-RA-QS-DIM-UNV	PT-24-L55/8FS-RA-QS-DIM-UNV

NOTES

- ¹ Lumen output based on 3500 CCT. Actual lumens may vary +/-5%, see page 2 for FIXTURE PERFORMANCE DATA.
- ² 4' length only.
- ³ 2' width only.
- ⁴ See page 3 for fieldseleCCT DETAILS.
- ⁵ Increases lumen output by 3%.
- ⁶ See [Technical Info](#) for Drywall Kit details.
- ⁷ See page 3 for ADDITIONAL CONTROL OPTIONS.
- ⁸ 2x2 and 2x4 only.
- ⁹ 1x4 only.
- ¹⁰ 2x2 & 2x4 only.
- ¹¹ 1x4 only.
- ¹² 2x2 & 2x4 only.
- ¹³ 4 per fixture. Optional for 1" grid installations. Required for 9/16" grid mounting.
- ¹⁴ See page 3 for SENSOR DETAILS.
- ¹⁵ See page 3 for SENSOR DETAILS.
- ¹⁶ Not available with emergency batteries.



FIXTURE PERFORMANCE DATA

	LED PACKAGE	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
1x4	L25	2441	19.8	123.2
	L37	3674	30.8	119.3
2x2	L50	4968	42.6	116.7
	L24	2378	20.8	114.3
2x4	L36	3595	30.9	116.5
	L37	3674	30.8	119.3
	L55	5460	47.3	115.5
	L62	6208	54.8	113.3


MULTIPLIER TABLE

COLOR TEMPERATURE	
CCT	CONVERSION FACTOR
3000K	0.94
3500K	1.00
4000K	0.95

- Photometrics tested in accordance with IESNA LM-79. Results shown are based on 25°C ambient temperature.
- Wattage shown is average for 120V through 277V input.
- Results based on 3500K, 80 CRI, actual lumens may vary +/-5%
- Use multiplier table to calculate additional options.

PHOTOMETRY


PT-24-L62/8FS-RA-DIM-UNV Total Luminaire Output: 6208 lumens; 55 Watts | Efficacy: 113 lm/W | 80 CRI; 3500K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	2375	2375	2375	
5	2339	2336	2323	223
15	2270	2278	2287	638
25	2000	2027	2052	923
35	1617	1668	1711	1041
45	1314	1387	1458	1062
55	956	1046	1130	938
65	619	733	833	724
75	293	451	558	474
85	60	199	228	186
90	0	0	0	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	1784	29
	0 - 40	2825	46
	0 - 60	4825	78
	0 - 90	6208	100
	0 - 180	6208	100


PT-14-L50/8FS-RA-DIM-UNV Total Luminaire Output: 4969 lumens; 43 Watts | Efficacy: 116 lm/W | 80 CRI; 3500K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	1811	1811	1811	
5	1852	1831	1804	173
15	1770	1765	1744	495
25	1619	1627	1607	744
35	1409	1427	1428	885
45	1124	1173	1191	895
55	804	884	921	785
65	516	611	627	585
75	229	321	335	326
85	35	58	68	80
90	0	0	0	


LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	1413	28
	0 - 40	2298	46
	0 - 60	3978	80
	0 - 90	4969	100
	0 - 180	4969	100

CROSS SECTIONS



FIXTURE DETAILS

BACKVIEW




ADDITIONAL CONTROL OPTIONS

Note: Lumen restrictions apply, consult product builder at hew.com/product-builder.

CATALOG NUMBER	DESCRIPTION
DRV	Driver prewired for non-dimming applications
DIM	Dimming driver prewired for 0-10V low voltage applications
DIM1	1% dimming driver prewired for 0-10V low voltage applications
DIM LINE	Line voltage dimming driver (TRIAC and ELV compatible, 120V only)
DIM TRC	Line voltage dimming driver (TRIAC compatible, 120V or 277V only)
DSR	Sensor-ready driver
SD40	40% step-dimming driver
SD50	50% step-dimming driver
DALI	DALI dimming driver
LTE LINE	Lutron Hi-lume 1% 2-wire dimming driver forward phase line voltage controls (120V only)
LDE1	Lutron Hi-lume 1% EcoSystem dimming LED driver
LDE5	Lutron 5-Series 5% EcoSystem dimming LED driver
VDO/DSR	Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC) and sensor-ready driver
VRF/DSR	Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF) and sensor-ready driver
VDO/DBI/LDE1	Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC), Lutron Hi-lume 1% EcoSystem dimming LED driver, and digital link interface
VDO/DBI/LDE5	Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC), Lutron 5-Series 5% EcoSystem dimming LED driver, and digital link interface
VRF/DBI/LDE1	Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF), Lutron Hi-lume 1% EcoSystem dimming LED driver, and digital link interface
VRF/DBI/LDE5	Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF), Lutron 5-Series 5% EcoSystem dimming LED driver, and digital link interface
ELDO SOLOB	EldoLED Solodrive, 0.1% dimming driver for 0-10V controls
ELDO SOLOB DALI	EldoLED Solodrive, 0.1% dimming driver for DALI controls
ELDO ECO1	EldoLED Ecodrive, 1% dimming driver for 0-10V controls
ELDO ECO1 DALI	EldoLED Ecodrive, 1% dimming driver for DALI controls

fieldselecCCT DETAILS



FLEXIBLE WHIP OPTIONS

All Williams recessed troffers are available with a flexible metallic wiring harness, factory-attached and hard-wired to the luminaire. See ordering information table.

Straight connectors are a snap-in type. Consult factory for wiring harness utilizing connectors secured by lock nuts, optional flex size, lengths, and other wire sizes or circuitry. Three-wire flex utilizes black, white, and green wire. Four-wire flex utilizes black, white, red, and green wire. Adding an emergency option requires an additional wire.

Williams fixtures are UL listed to provide factory-installation of several manufacturers' modular wiring devices. Consult factory for availability and ordering information.

DESIGNATION	DESCRIPTION	DRIVER
F338	6' of 3/8" flex, (3) No. 18 AWG wires with (2) straight connectors	DRV, LTE LINE
F348	6' of 3/8" flex, (4) No. 18 AWG wires with (2) straight connectors	SD40
F334	6' of 3/8" flex, (3) No. 14 AWG wires with (2) straight connectors	DRV, LTE LINE
F344	6' of 3/8" flex, (4) No. 14 AWG wires with (2) straight connectors	SD40
F358	6' of 3/8" flex, (5) #18 AWG wires with (2) straight connectors	DIM, DALI

SENSOR DETAILS

