

CATALOG #: \_\_\_\_\_

Type: \_\_\_\_\_

PROJECT: \_\_\_\_\_

## FEATURES

- Heat and impact-resistant tempered glass lens
- Heavy-duty die-cast aluminum construction
- Fully gasketed for wet locations
- Provides full cutoff. Meets dark sky requirements.

## SPECIFICATIONS

- HOUSING – Die-cast aluminum.
- LENS – Tempered, flat, clear glass.
- FINISH – Powder coated finish on heavy-duty die-cast housing. Dark bronze finish only.
- ELECTRICAL – Electronic 120-277V or 347/480V dimmable driver. Metal core PCB LED array.
- MOUNTING – Wall mounts directly over a 4" maximum recessed outlet box.
- LISTINGS –
  - cCSAus listed to STD22.2 No. 250.0 certified as luminaire suitable for wet locations. 40°C maximum ambient operating temperature.
- WARRANTY – 5-year limited warranty.

## ORDERING EXAMPLE: WPRD - L43/850 - OPTIONS - DIM - UNV

### ORDERING INFO

SERIES	LUMENS	CRI	CCT	OPTIONS	DRIVER
WPRD <sup>(1)</sup>	L43 4,300lm	8 80	50 5000K	<b>SF</b> Single fuse <sup>(2)</sup> <b>DF</b> Double fuse <sup>(3)</sup> <b>SP2</b> 2.5kV surge protection	<b>DIM</b> Dimming driver prewired for 0-10V low voltage applications

### VOLTAGE


120	120V
208	208V
240	240V
277	277V
UNV	120-277V
347	347V
480	480V

## NOTES

- <sup>1</sup> This fixture does not comply with Buy American/ARRA and similar regulatory programs.
- <sup>2</sup> 120V or 277V only; must specify voltage.

- <sup>3</sup> 208V or 240V only; must specify voltage.

## FOOTCANDLE ESTIMATOR & DISTRIBUTION




Footcandle calculations based on standard building reflectance of .10 with a ground reflectance of .0 and a light loss factor of .90.

Fixture installed at 12' mounting height.

- Wattage: 52
- Efficacy: 83.6 lm/w
- Flux: 4305 lm
- CRI: 80
- CCT: 5081
- BUG Ratings: B1-U1-G1

## MOUNTING DETAILS

### BACKVIEW



### WALL MOUNT BOLT CIRCLE PATTERN

