

INTEGRAL CONTROLS GUIDE

TROFFERS, SURFACE & WRAPS



CONTENTS

NETWORKED CONTROLS

Avi-on	1
Lutron Athena	2
Lutron Vive	2
Wattstopper DLM	3
Wattstopper Plus (By Encelium)	3

STAND-ALONE SENSOR

Leviton PIR Motion & Daylight	4
-------------------------------------	---

Fixture Compatibility

.....	5
-------	---

NETWORKED CONTROLS

ADDITIONAL CONTROLS AVAILABLE, CONSULT FACTORY.

AVI-ON

WIRELESS SYSTEM





CATALOG NUMBER	DESCRIPTION	LED PACKAGE	COMPATIBLE DRIVER
AVI-LVFA	Wireless fixture control	Static White	DA
AVI-LVFA2	Wireless fixture control	Tunable White	DA
AVI-LVFA-CS2-PIR	Wireless fixture control with PIR motion and daylight sensor	Static White	DA
AVI-LVFA2-CS2-PIR	Wireless fixture control with PIR motion and daylight sensor	Tunable White	DA



SENSOR DETAILS

Mounting Heights: 8' – 10'
Dimensions: 13/16" x 2-1/4"



INTEGRAL CONTROLS GUIDE

TROFFERS, SURFACE & WRAPS

LUTRON ATHENA




WIRELESS SYSTEM

CATALOG NUMBER	DESCRIPTION	LED PACKAGE	COMPATIBLE DRIVER
AWNR	Wireless node fixture control, RF only	Static or Tunable White	DA, DSR, LD2
AWNR-BL	Wireless node fixture control, RF only, black finish	Static or Tunable White	DA, DSR, LD2
AWNS	Wireless node fixture control, RF with daylight and occupancy sensor	Static or Tunable White	DA, DSR, LD2
AWNS-BL	Wireless node fixture control, RF with daylight and occupancy sensor, black finish	Static or Tunable White	DA, DSR, LD2



SENSOR DETAILS

Mounting Heights: 8' – 12'
Dimensions: Ø1-1/8"



LUTRON VIVE




DWIRELESS SYSTEM

CATALOG NUMBER	DESCRIPTION	LED PACKAGE	COMPATIBLE DRIVER
VRF	Wireless fixture control, RF only (DFCSJ-OEM-RF)	Static White	DSR
VRF/DBI	Wireless fixture control, RF only (DFCSJ-OEM-RF) and digital link interface	Static White	LDE1
VDO	Wireless fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC)	Static White	DSR
VDO/DBI	Wireless fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC) and digital link interface	Static White	LDE1



SENSOR DETAILS

Mounting Heights: 8' – 12'
Dimensions: 2-11/16" x 1"



INTEGRAL CONTROLS GUIDE

TROFFERS, SURFACE & WRAPS

WATTSTOPPER DLM



WIRED & WIRELESS SYSTEMS

CATALOG NUMBER	DESCRIPTION	LED PACKAGE	COMPATIBLE DRIVER
WS-LMFC-011-1RJ	Wired on/off/dim fixture control, one RJ45 jack	Static White	DIM1
WS-LMFC-011-2RJ	Wired on/off/dim fixture control, two RJ45 jacks	Static White	DIM1
WS-LMFS-601	Wireless on/off/dim fixture control with motion and daylight sensor	Static White	D4I



SENSOR DETAILS

Mounting Heights: 8' – 12'
Dimensions: ø1-5/16"



WATTSTOPPER PLUS (BY ENCELIUM)



WIRED & WIRELESS SYSTEMS

CATALOG NUMBER	DESCRIPTION	LED PACKAGE	COMPATIBLE DRIVER
WS-ILCM	Wired fixture control	Static White	DIM1
WS-ILCMDR	Wired fixture control, damp rated	Static White	DIM1
WS-WCM	Wireless fixture control	Static White	DIM1
WS-WCMDR	Wireless fixture control, damp rated	Static White	DIM1
WS-CLM	CLM wireless fixture control	Tunable White	DA, D4I
WS-CLM-PIR	SensiLum wireless fixture control with PIR motion and daylight sensor	Tunable White	DA, D4I



SENSOR DETAILS

Mounting Height: 20' max
Dimensions: ø7/8"



INTEGRAL CONTROLS GUIDE

TROFFERS, SURFACE & WRAPS


STAND-ALONE SENSOR

LEVITON PIR MOTION & DAYLIGHT





SENSOR ONLY, NO INTEGRAL CONTROLS

CATALOG NUMBER	DESCRIPTION	LED PACKAGE	COMPATIBLE DRIVER
LV-ZLS05-ILW	PIR motion and daylight sensor	Static White	DA
ZLSOR-RA1	Optional remote controller for ZLS05 sensor. Please specify quantity required per project. Ordered and shipped separately.		



SENSOR DETAILS

Mounting Heights: 8' – 10'
Dimensions: ø1-5/16"



INTEGRAL CONTROLS GUIDE

TROFFERS, SURFACE & WRAPS

Fixture Compatibility

AVI-ON		LEVITON	LUTRON				WATTSTOPPER					
			ATHENA		VIVE		DLM		PLUS			
			AWNR	AWNS	VRF	VDO	LMFC	LMFS	ILCM	WCM	CLM	CLM-PIR
RECESSED	50	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AHT	✓			✓	✓	✓	✓		✓	✓	✓
	AP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AT1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AT2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	AT3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	BAR	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	BP											
	DI	✓			✓	✓	✓			✓	✓	✓
	DI-AR	✓			✓	✓	✓	✓		✓	✓	✓
	DIL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	FRM	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	FT											
	HET	✓			✓	✓	✓	✓		✓	✓	✓
	HET-AR	✓			✓	✓	✓	✓		✓	✓	✓
	HETL	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	LPT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	LT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	LT-AR	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PTDC	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PT-MET	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PTR	✓	✓	✓	✓	✓	✓	✓			✓	✓
	RND	✓			✓	✓		✓		✓	✓	✓
	SQR	✓			✓	✓		✓		✓	✓	✓
	V50	✓			✓	✓		✓		✓	✓	✓
	VDIL	✓			✓	✓		✓		✓	✓	✓
SURFACE	11	✓	✓	✓	✓	✓			✓	✓		✓
	12	✓	✓	✓	✓	✓			✓	✓		✓
	1SF	✓										
	ASM	✓			✓				✓			
	ATS1	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
	ATS2	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
	ATS3	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
	DIS	✓			✓				✓			✓
	HES	✓			✓				✓			✓
	PTS	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓
	RNDS	✓			✓				✓			
	SL	✓			✓				✓	✓	✓	✓
WRAPS	NW											
	AW	✓	✓	✓	✓	✓			✓	✓		✓
	AVX	✓							✓			✓
	17	✓				✓			✓			
	18	✓				✓			✓			
	39	✓				✓			✓			

